

FREEFIELD LTD.

Ottawa, Ontario

ACOUSTIC ASSESSMENT FOR THE HIGHLAND LINE PIT LANARK HIGHLAND TOWNSHIP LANARK COUNTY ONTARIO

Prepared for

Thomas Cavanagh Construction Limited

Prepared by

Freefield Ltd.

5th September 2025

ACOUSTIC ASSESSMENT FOR THE HIGHLAND LINE PIT LANARK HIGHLAND TOWNSHIP, LANARK COUNTY, ONTARIO

Executive Summary

Thomas Cavanagh Construction Limited (Cavanagh) is applying to the Ministry of Natural Resources and Forestry, MNRF, for a license under the Aggregate Resources Act, ARA, for the Highland Line Pit, Class A, Sand Pit (below water), to be located at Part of Lot 5, Concession 10, Lanark Highland Township, Lanark County, Ontario, as shown in Figures 1 and 2.


The North American Industry Classification System (NAICS) code of the facility is 212323.

The MNRF license application requires the submission of an Acoustic Assessment Report of the proposed operation. Freefield Ltd. has been retained by Cavanagh to complete this acoustic assessment.

The acoustic assessment has been carried out according to the applicable Ministry of Environment, Conservation and Parks (MECP) Noise Assessment Guidelines, including NPC-300, published August 2013. The assessment considers the impact on nearby noise sensitive lands, including existing residences and vacant land zoned for potential noise sensitive use, of noise generated by all on-site equipment operations, including extraction operations by loaders or excavators, aggregate processing operations by a crushing plant, screening plant and wash plant, loading operations by loaders, site preparation and maintenance by an excavator and truck movements used for the shipping of product off-site on a 24-hour basis. The site is not a significant source of vibration hence an assessment of vibrations is not required.


Noise impacts have been predicted and compared to the MECP sound level limits as set out in NPC-300. Where applicable, noise mitigation measures such as barriers and limits to operations have been designed to ensure all operations comply with the applicable sound level limits.

Assessment methodology is provided in Section 1. A detailed description of the facility and its operations is provided in Section 2. Noise sources associated with operations at the pit are summarized in Section 3. Noise sensitive receptors are described in Section 1 and Section 4, with Section 5, 6 and 7 detailing applicable assessment criteria, an assessment of noise impacts and recommended mitigation measures.



Version Control


Title	Comments	Prepared By	Issue Date
Acoustic Assessment for the Proposed Highland Line Pit Lanark Highland Township, Ontario	Submitted with initial ARA License Application	Freefield Ltd.	23 rd September 2022
Acoustic Assessment for the Proposed Highland Line Pit Lanark Highland Township, Ontario	Updated to address MNRF comments related to recommended enclosure and silencer at generator	Freefield Ltd.	29 th April 2024
Acoustic Assessment for the Proposed Highland Line Pit Lanark Highland Township, Ontario	Updated to address Peer Review comments, dated 14 th April 2025.	Freefield Ltd.	5 th September 2025 (This version)



ACOUSTIC ASSESSMENT FOR THE HIGHLAND LINE PIT LANARK HIGHLAND TOWNSHIP, LANARK COUNTY, ONTARIO

Table of Contents

Section	Page
Executive Summary	i
Version Control	ii
Table of Contents	iii - vi
1.0 Introduction	1 - 3
2.0 Facility Description	4 - 6
3.0 Noise Source Summary	7
4.0 Point of Reception Summary	8
5.0 Assessment Criteria, Performance Limits	9
6.0 Impact Assessment	10 - 12
7.0 Mitigation Measures	13 - 14
8.0 Conclusions	15
References	16




Tables

Table 1: Points of Reception Summary Table	17
Table 2: Noise Source Summary Table	
Table 3: Exclusion Limit Values for One-Hour Equivalent Sound Level (Leq, dBA) at Outdoor Points of Reception	
Table 4: Exclusion Limit Values for One-Hour Equivalent Sound Level (Leq, dBA) at Plane of Window of Noise Sensitive Spaces	
Table 5: Applicable One Hour Sound Level Limits	
Table 6.1: Acoustic Assessment Summary for Worst Case Operation – Before Mitigation	
Table 6.2: Acoustic Assessment Summary for Worst Case Operation – After Mitigation	
Table 7: Recommended Noise Barriers	

Figures

29

Figure 1: Scaled Area Location Plan showing Receptor Locations
Figure 2: Detail Site Layout & Surface Elevation Contours (elevation contours based on Land Information Ontario (LIO), Provincial Digital Elevation Model, at 2-meter intervals)
Figure 3: Scenario 1: Worst Case, Extraction Area 1 – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only)
Figure 4: Prediction Results, Scenario 1: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
Figure 5: Scenario 2: Worst Case, Extraction Area 1 - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 5 – (Day only)
Figure 6: Prediction Results, Scenario 2: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
Figure 7: Scenario 3: Worst Case, Extraction Area 2 - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 6 & 7 – (Day only)
Figure 8: Prediction Results, Scenario 3: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
Figure 9: Scenario 4: Worst Case, Extraction Area 2 - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only)
Figure 10: Prediction Results, Scenario 4: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
Figure 11: Scenario 5: Worst Case, Extraction Area 1 – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only)
Figure 12: Prediction Results, Scenario 5: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation



- Figure 13: Scenario 6: Worst Case, **Extraction Area 1** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 5 – (Day only)
- Figure 14: Prediction Results, Scenario 6: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 15: Scenario 7: Worst Case, **Extraction Area 2** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 6 & 7 – (Day only)
- Figure 16: Prediction Results, Scenario 7: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 17: Scenario 8: Worst Case, **Extraction Area 2** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only)
- Figure 18: Prediction Results, Scenario 8: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 19: Scenario 9 Worst Case, **Extraction Area 1** – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only)
- Figure 20: Prediction Results, Scenario 9: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 21: Scenario 10: Worst Case, **Extraction Area 1** – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only)
- Figure 22: Prediction Results, Scenario 10: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 23: Detail site plan showing location of site berms and barrier requirements
- Figure 24: Detail plan at Mobile Screening Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 1**
- Figure 25: Detail plan at Wash Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 1**
- Figure 26: Detail plan at Mobile Crushing Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 1**
- Figure 27: Detail plan at Mobile Crushing Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 2**

Appendix 1 Zoning Maps

Zoning Map: Zoning By-law for the Township of Lanark Highlands, Dalhousie Township and North Sherbrooke, Schedule A2, By-law no. 2003-451 (source: Township of Lanark Highlands)

Appendix 2 Acoustic Modeling Details

Table A2.1	Point of Reception Location Table
Table A2.2	Point Sources
Table A2.3	Line Sources





Table A2.4	Noise Barriers
Table A2.5	Noise Source Library
Table A2.6	Noise Measurement Data
Table A2.7.1	Point of Reception Impacts by Source for Scenario 1 – After Mitigation
Table A2.7.2	Point of Reception Impacts by Source for Scenario 2 – After Mitigation
Table A2.7.3	Point of Reception Impacts by Source for Scenario 3 – After Mitigation
Table A2.7.4	Point of Reception Impacts by Source for Scenario 4 – After Mitigation
Table A2.7.5	Point of Reception Impacts by Source for Scenario 5 – After Mitigation
Table A2.7.6	Point of Reception Impacts by Source for Scenario 6 – After Mitigation
Table A2.7.7	Point of Reception Impacts by Source for Scenario 7 – After Mitigation
Table A2.7.8	Point of Reception Impacts by Source for Scenario 8 – After Mitigation
Table A2.7.9	Point of Reception Impacts by Source for Scenario 9 – After Mitigation
Table A2.7.10	Point of Reception Impacts by Source for Scenario 10 – After Mitigation
Table A2.8	Distance Source to Point of Reception
Table A2.9	Sample Calculation

Appendix 3: Instrument Calibration Certificates

Appendix 4: Manufactures Data

Resumes: Hugh Williamson, Michael Wells



ACOUSTIC ASSESSMENT FOR THE HIGHLAND LINE PIT LANARK HIGHLAND TOWNSHIP, LANARK COUNTY, ONTARIO

1.0 Introduction

Thomas Cavanagh Construction Limited (Cavanagh) is applying to the Ministry of Natural Resources and Forestry, MNRF, for a license under the Aggregate Resources Act, ARA, for the Highland Line Pit, Class A, Sand Pit (below water), to be located at Part of Lot 5, Concession 10, Lanark Highland Township, Lanark County, Ontario, as shown in Figures 1 and 2 (the facility).


The North American Industry Classification System (NAICS) code of the facility is 212323.

This report describes an assessment, carried out by Freefield Ltd., of the potential impact of noise from operations at the facility on nearby noise sensitive receptors in accordance with MECP guidelines for stationary noise sources.^{1,2}

This report has been prepared in accordance with the MECP Document NPC-233, *Information to be Submitted for Approval of Stationary Sources of Sound*, October 1995. Noise from the facility is assessed according to MECP Documents: NPC-300, *Stationary and Transportation Sources – Approval and Planning*, August 2013.¹ This report follows the recommended format contained in, *Sample Application Package, Basic Comprehensive Certificate of Approval (Air and Noise)*, July 2009.²

The noise assessment methodology is summarised below.

- Identification of noise sensitive receptors in the vicinity of the facility. Potential noise sensitive receptors include residences, motels, places of worship, schools, hospitals and vacant land zoned for potential noise sensitive use.
- Determination of the MECP sound level limits¹ which apply at each of the noise sensitive receptors.
- Identification of the sources of noise that will arise from the facilities operations. In the current study, the strengths of the various noise sources were obtained from noise measurements of the proposed equipment in operation at the Cavanagh Pine Grove Pit carried out in October 2019 and from a database of noise measurements of similar operations at other aggregate operations in Ontario by Freefield Ltd.



- Based on the strengths of the individual noise sources, noise levels due to the facilities operations are predicted at nearby noise sensitive receptors using a prediction procedure⁶ which is favoured by the MECP. The MECP methodology requires that compliance be assessed under predictable “worst case” conditions for normal operations.
- Assessment of compliance of the noise due to the facilities operations with MECP sound level limits. Where appropriate mitigation measures are recommended such that compliance, with MECP sound level limits, is achieved at all receptors.

Note that this assessment considers all significant noise sources in operation on the site. The site is not a significant source of vibration; hence, an assessment of vibrations is not required.

Surrounding Lands, Acoustic Environment and Noise Sensitive Receptors

The facility is located in a predominantly rural area, on the south sides of Highland Line Road, approximately 2.8 km west of Country Road 12, in Lanark Highland Township, Lanark, Ontario.

The site is bisected by Anderson Lane into an east and west extraction area. The extraction areas consist of an unexcavated sand deposit. The site rises in a southerly direction from Highland Line Road to a ridge approximately 20 m high located in the southern portion of each extraction area. The land surrounding the facility consists of undulating topography with moderate changes in elevation, plus minus 20 m.

Note that directions in this report are referenced to site north as shown in Figure 1.


The legal description of the land occupied by the facility is as follows:

**Part of Lot 5,
Concession 10,
Lanark Highland Township,
Lanark County, Ontario**

A location plan showing the site with respect to the surrounding area is provided in Figure 1. A site layout plan, showing the sites detailed arrangement and elevation contours, is provided in Figure 2. A land use zoning map is provided in Appendix 1.

The site is zoned Mineral Aggregate Reserve – Holding Zone (MAR-h) and Rural (RU) as shown on the Zoning Map, Appendix 1. It is noted, while the proposed licensed area will be located fully within Part of Lot 5 the property boundary incorporates an area to the south located on Part of Lot 4, as shown on Figure 1, 2 and Appendix 1.

To the north of the site the land is zoned Rural (RU) with areas of Limited Services Rural (LSR) and Mineral Aggregate Resources Reserve – Holding Zone (MAR-h) and Environmental Protection (Organic Soils) zoned land. An existing pit lies immediately north of the site on the northern side of Highland Line Road with a number of existing residences, and vacant lots zoned



for potential noise sensitive use, located in this direction with access via McDonalds Corner Road, 10th Concession Road, 11th Concession Road Dalhousie, Camerons Place and Highland Line Road. The closest existing residences and potential future residences, on vacant land zoned RU and LSR, in this direction have been selected as noise sensitive receptors in the following assessment.

To the east of the site the land is zoned Mineral Aggregate Resources Pit (MXP) and Limited Services Rural (LSR). An existing licensed pit on land zoned MXP and a small number of residences and seasonal hunt camps, fronting Barbers Lake with access via Leo Jay Road, exist in this direction. The closest existing residences and seasonal hunt camps in this direction have been selected as noise sensitive receptors in the following assessment.


To the south of the site the land is zoned Rural (RU) and Limited Services Rural (LSR). An existing residence and a vacant lot zoned for potential noise sensitive use lie in this direction with access via Anderson Lane and Concession Road 11 Dalhousie respectively. The closest existing residence and vacant lot zoned for potential noise sensitive use in this direction have been selected as noise sensitive receptors in the following assessment.

To the west of the site the land is zoned Rural (RU) with pockets of Mineral Aggregate Resources Reserve – Holding Zone (MAR-h). A small number of residences exist in this direction fronting Highland Line Road. In addition, Wheelers Pancake House and Sugar Camp (camp) lie in this direction, while primarily a restaurant and day camp for school tours, also provides opportunities for accommodation in the historic farmhouse. As such the closest existing residence and camp in this direction have been selected as noise sensitive receptors in the following assessment.

Where receptors have been located on vacant land zoned for potential noise sensitive use i.e. a possible future residence located on land zoned rural, the location selected for assessment is consistent with the existing pattern of development in the area.

The noise sensitive noise sensitive receptors, which have been selected for detailed analysis, are shown in Figure 1. These were selected as being the receptors most likely impacted by noise from the facilities operations. Other noise sensitive receptors are at greater distances and will be less affected by noise from the facility.

Table 1 lists the noise sensitive receptors selected for analysis.



2.0 Facility Description

The proposed Highland Line Pit will produce various grades of sand and aggregate with an annual production limit of 500,000 tonnes per year.

The site is divided into an east extraction area (Extraction Area 1) and west extraction area (Extraction Area 2) by Anderson Lane as shown on Figure 1 and 2.

Excavated raw material will be extracted in each extraction area by excavators and loaders which transport the raw material to a screening plant located near the lift face. After screening processed sand is stockpiled using conveyors and stackers. A loader or excavator then loads the processed sand from stockpiles onto highway trucks which are used to deliver the product off-site. The screening plant has a maximum throughput capacity of 200 tonnes per hour.

At certain times a wash plant may be used in place of the mobile screening plant to process raw material. The wash plant has a maximum throughput capacity of 200 tonnes per hour.

The larger stones and rocks which are separated by the screening plant or wash plant will be stockpiled before being transferred to a mobile crushing plant which is brought to site as needed. After crushing, processed aggregate will be stockpiled using conveyors and stackers. A loader or excavator then loads the processed aggregate from stockpiles onto highway trucks which are used to deliver the product off-site.

Additional material may be brought on site as needed, stored and processed, before being shipped off site.

Extraction of the pit will take place in a number of lifts up to 20 m in height, possibly in benches.


The existing ground elevation and pit floor of the first lift down in each extraction area will be at an approximate elevation of 188 mASL. The ground water table lies at an approximate elevation of 186 mASL.

Extraction will commence in the north of each extraction area in the area adjacent to Highland Line Road near the site entries as shown on Figure 2 and proceed to the setback limits in a south, east and west direction in each extraction area.

Access for shipping processed sand and aggregate, in each extraction area, is from the site entrances off Highland Line Road as shown in Figure 2.

The following equipment will be operated on-site and is included in this assessment as significant sources of noise:

- One mobile screening plant, with associated conveyors and stackers,
- One wash plant, with associated conveyors, stackers and diesel generator,
- One mobile crushing plant, brought to site occasionally, when required,



- Up to six loaders or excavators,
- Highway trucks used to ship the product off site,
- Portable equipment for site preparation and rehabilitation, including excavators, hydraulic shovels, dozers and scrapers.

A description of each operation follows:

Mobile Screening Plant

A mobile screening plant (mobile screener) will be brought to site as needed and located near the extraction face. The mobile screener consists of a hopper (feed bin), screen deck, diesel engine, magnetic separator and conveyors. Overburden, soil, sand and aggregate are fed through the screening plant to produce various grades of product before being stockpiled, using stackers and conveyors, and processed for shipping off site. Oversized aggregates separated in the screening process are stockpiled before being taken to the mobile crushing plant for further processing. Typically, two loaders and two excavators are used to extract material from the lift face to feed the screening plant and fill trucks from the stockpiles for shipment off-site.

The mobile screening plant operates only during daytime hours (07:00 – 19:00).

Wash Plant

A wash plant is used to process extracted sand and separate it into various grades of aggregate. The major components of the wash plant include a hopper (feed bin), dry screen deck, a wet screen deck, a classifier, two double screw material washers, a dewatering derrick and conveyors and stackers. Typically, associated operations include loaders used to supply raw material to the plant and to load trucks from stockpiles for delivery off-site and a diesel generator used to provide power to the plant.

The wash plant operates only during daytime hours (07:00 – 19:00).

Mobile Crushing Plant


A mobile crushing plant (crusher) is brought to site as needed and located in each extraction area in location shown on Figure 2. The plant consists of a hopper (feed bin), primary and secondary crushing units, a diesel engine, vibrating screens, a magnetic separator and conveyors. Typically, associated operations include one loader and excavator.

The mobile crushing plant operates only during daytime hours (07:00 – 19:00).

Loaders and Excavators

Typically, loaders and excavators are required on-site for the following:

- Extracting raw material from the extraction face,
- Loading extracted material onto trucks for delivery to the mobile crushing plant,
- Loading sand from stockpiles into the hoppers to feed the mobile screening plant,
- Loading processed sand and aggregate on to trucks for shipping off-site,
- Generally pushing around rock and aggregate to maintain the site in a safe state,



- Removing overburden and site preparation,

The loaders and excavators operate only during daytime hours (07:00 – 19:00).

Highway Trucks


Highway trucks are used for shipping processed sand and aggregate off site and as needed to deliver oversized material separated in the screening process to stockpiles located near the mobile crushing plant in each extraction area. Based on the annual tonnage it is assumed 15 loads per hour in total are shipped off-site from the screening plant, wash plant and / or mobile crushing plant during periods of maximum capacity during the proposed daytime period of operation. The speed limit for trucks on site is 30 km/h. The use of Jake brakes (compression assisted brakes) is forbidden on site.

Trucks used for shipping and delivery of product and the associated on-site truck movements take place only during daytime hours (07:00 – 19:00).

Portable equipment for site preparations and rehabilitation

Portable construction equipment will be used occasionally for site preparation (e.g. land clearing and construction of berms) and rehabilitation. This equipment would typically include excavators, hydraulic shovels, dozers and scrapers. To minimize the impact of noise during site preparation and rehabilitation, the construction equipment used, excavators, bulldozers, etc., will comply with MECP Publication NPC-115,⁵ Construction Equipment, August 1978. This publication gives noise standards to be met by construction equipment in Ontario.

Site preparation and rehabilitation activities will take place only during daytime hours (07:00 – 19:00).




Hours of Operation

Daytime Operations (07:00 – 19:00) - During the daytime period, all significant noise sources are assumed to be in operation and include the following:

- One Mobile Screening Plant,
- One Wash Plant,
- One Mobile Crushing plant,
- Up to six loaders or excavators carrying out extraction, stockpiling and loading operations,
- On-site truck movements used to deliver material to the mobile crushing plant and ship processed product off-site.

Evening and Nighttime Operations (19:00 – 07:00) – During the evening and nighttime period the pit does not operate.



3.0 Noise Source Summary

The following noise sources have been used to model noise generated by operations at the Highland Line Pit. In brackets are the shortened names of the noise sources as used in the acoustic model. The characteristics of these sources, as used in acoustic modelling, are summarized in Table 2.

- One Mobile Screening Plant (Source: Screener),
- One Wash Plant (Source: Washplant),
- One diesel generator used to provide power to the wash plant (Source: Generator),
- One Mobile Crushing Plant (Source: Crusher),
- Three Loaders (Source: Loader_1, Loader_2 and Loader_3)
- Three Excavators (Source: Excavator_1, Excavator_2 and Excavator_3)
- On-site truck movements (Source: IHR_1 and IHR_2).

The noise modelling considers various scenarios relating to different areas of operation as described in Section 6.0. For each scenario, the locations of the noise sources are selected for worst case noise impacts.

The strengths of the noise sources, i.e. the sound powers shown in Table 2 and used in this analysis, are taken from noise measurements of the mobile screening plant in operation at the Cavanagh Pine Grove Pit in October 2019, the wash plant in operation at Cavanagh Lanark Quarry in August 2020 and from a database of noise measurements by Freefield Ltd. of similar operations made at other aggregate operations in Ontario.

A Brüel & Kjær Type 2270 sound level meter was used for all noise measurements. Field calibrations, using a Brüel & Kjær 4231 field calibrator, and battery checks were carried out before and after each measurement series. In no case did the field calibration vary by more than 0.1 dB over a series of measurements. In addition, the sound level meters, and the field calibrator are laboratory calibrated on an annual basis. Copies of the relevant calibration certificates are included in Appendix 3.


The weather conditions during the measurements were suitable for outdoor noise measurements (variable winds of less than 20 km/h, skies generally clear with relatively low humidity). A windshield was used during noise measurements.

Noise from the highway trucks, and associated on-site haul routes, are estimated using the moving point source method and modelled as a loop indicating the worst-case on-site truck movements.

Insignificant noise sources:

Conveyors, stackers and noise from employee or service vehicles have been assessed as insignificant noise sources in this analysis.

Refer to Figures 3, 5, 7, 9, 11, 13, 15, 17, 19 and 21 for locations of sources for the worst-case modes of operation analysed.



4.0 Point of Reception Summary

A total of fifteen nearby noise sensitive receptors have been selected for detailed noise evaluation.

These existing and potential future residences on vacant land zoned for potential noise sensitive use are those closest to the proposed pit in all directions and represent the worst-case noise impacts in comparison to other nearby or more distant noise sensitive receptors.


The fifteen points of reception selected for analysis, POR 1 to POR 15, are shown in Figure 1 and listed in Table 1.

As per MECP Guideline NPC-300, two points of reception (POR) have been selected at each noise sensitive receptor for which worst case sound levels have been calculated.

POW – Plane of window (POW) points of reception are located on the dwelling or noise sensitive building, typically 2 m above ground for single storey dwellings and 4.5 m above ground for two storey dwellings.

OPR – Outdoor Point of Reception, an area on the property of the residence. For large properties, the OPR point of reception can be up to 30 m from the dwelling at a height of 1.5 m above ground.

Where receptors have been located on vacant land zoned for potential noise sensitive use i.e. a possible future residence located on land zoned rural, the location selected for assessment are consistent with the existing pattern of development in the area.



5.0 Assessment Criteria, Performance Limits

Sound level limits, as specified in the MECP guideline NPC-300¹, depend on the acoustical classification of the area as Class 1, 2, 3 or 4.

Class 1 area 'an area with an acoustical environment typical of a major population centre, where the background sound level is dominated by the activities of people, usually road traffic, often referred to as urban hum.'

Class 2 area 'an area with an acoustical environment that has qualities representative of both Class 1 and Class 3 areas: sound levels characteristic of Class 1 during daytime (07:00 to 19:00 or to 23:00 hours); and low evening and night background sound level defined by natural environment and infrequent human activity starting as early as 19:00 hours (19:00 or 23:00 to 07:00 hours).'

Class 3 area 'a rural area with an acoustical environment that is dominated by natural sounds having little or no road traffic, such as: a small community; agricultural area; a rural resort area such as a cottage or resort area; or, a wilderness area.'

Class 4 area 'an area or specific site that would otherwise be defined as Class 1 or 2 and which: is an area intended for development with new noise sensitive land use(s) that are not yet built; is in proximity to existing, lawfully established stationary source(s); and, has formal confirmation from the land use planning authority with the Class 4 area classification which is determined during the land use planning process. Additionally, areas with existing noise sensitive land use(s) cannot be classified as Class 4 areas.'


Due to the relatively low levels of road traffic along Highland Line Road and other nearby roads the area in which all receptors are located is classified as Class 3 Area.

The applicable outdoor sound level limit at a point of reception is the higher of the applicable exclusion limit value, presented in Tables 3 and Table 4, or the background sound level for that point of reception. Background sound level means the sound level that is present in the environment produced by noise sources other than the source under assessment.

A background noise assessment was not carried out, hence, the levels given in the Tables 3 and 4 are taken as the sound level limits at all points of reception for the purpose of this assessment according to their location in a Class 3 Area.

The applicable sound level limits for each point of reception are set out in Table 5.

Sound levels are assessed in terms of the 1-hour equivalent sound level, L_{eq} , effectively the average sound level over each hour. All sound levels are A-weighted, A-weighting being a frequency weighting which represents sensitivity of human hearing to sounds of differing frequencies.



6.0 Impact Assessment

Noise levels have been predicted at the noise sensitive receptors using “predictable worst case” assumptions under normal operations and using ISO 9613-2 sound propagation methodology⁶ as implemented in the sound prediction software Cadna-A, Version 2025. The “predictable worst case” is interpreted as meaning the greatest noise impact anticipated under normal operating conditions. The ISO methodology provides a conservative (i.e. high) estimate of the noise level at a receptor taking into account adverse wind and meteorological conditions.

The estimation method includes the following:

- Distance attenuation is based on spherical spreading.
- Atmospheric attenuation.
- Ground attenuations, as appropriate.
- Barrier attenuation, as appropriate.

In order to consider cases of worst noise impacts, ten operational scenarios have been modeled. In general, the worst impacts are those which occur when all equipment is operating concurrently.

The following ten worst case scenarios are presented in this report and form the basis for the recommended mitigation measures and assessment of compliance to MECP criteria:

*Scenario 1: Worst Case, **Extraction Area 1** – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only) – Figure 3 and 4.*


*Scenario 2: Worst Case, **Extraction Area 1** - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 5 (Day only) – Figure 5 and 6.*

*Scenario 3: Worst Case, **Extraction Area 2** - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 6 & 7 (Day only) – Figure 7 and 8.*

*Scenario 4: Worst Case, **Extraction Area 2** - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only) – Figure 9 and 10.*

*Scenario 5: Worst Case, **Extraction Area 1** – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only) – Figure 11 and 12.*

*Scenario 6: Worst Case, **Extraction Area 1** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 5 (Day only) – Figure 13 and 14.*



Scenario 7: *Worst Case, **Extraction Area 2** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 6 & 7 (Day only) – Figure 15 and 16.*

Scenario 8: *Worst Case, **Extraction Area 2** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only) – Figure 17 and 18.*

Scenario 9: *Worst Case, **Extraction Area 1** – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only) – Figure 19 and 20.*

Scenario 10: *Worst Case, **Extraction Area 1** – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only) – Figure 21 and 22.*


In Table 6.1 and 6.2, estimated noise levels at the nearest receptors for the worst-case scenarios, before and after mitigation, are compared with the applicable sound level limits. More detailed estimates, for all sources and scenarios, are contained in the Point of Reception Noise Impact Tables in Appendix 2, Tables A2.7.1 to A2.7.10 and Table A2.8.

It can be seen that the sound level limits are met at all noise sensitive points of reception, POR 1 to POR 15, for worst case operating conditions during the proposed daytime period of operation 7 am to 7 pm (07:00 to 19:00).

Details of acoustic modeling are provided in Appendix 2. Figures 4, 6, 8, 10, 12, 14, 16, 18, 20 and 22 show predicted noise contours, after mitigation, for each mode of operation analyzed.

Statement of Compliance

It is concluded that, with the recommended mitigation measures detailed in section 7.0, noise impacts from operations at the Highland Line Pit will be in compliance with MECP Environmental Noise Guidelines¹ for the proposed daytime period of operation 7 am to 7 pm (07:00 to 19:00).



7.0 Mitigation Measures (Site Plan Recommendations)

Noise mitigation measures for the Highland Line Pit operations are detailed below.

The predicted noise impacts in Tables A2.7.1 to A2.7.10 are based on the implementation of the following mitigation measures:

7.1 Noise Barriers and Berms:


- 7.1.1 Noise barriers and berms are to be provided as per Table 7 and Figure 23, 24, 25, 26 and 27
- 7.1.2 Noise barriers and berms are to be solid, having no gaps, and are to have a surface density of no less than 20 kg/m². Examples of suitable barriers or berms are as follow:
 - 7.1.2.1 Lift face or existing terrain;
 - 7.1.2.2 Earth, gravel or aggregate berms or stockpiles;
 - 7.1.2.3 Concrete or brick walls;
 - 7.1.2.4 Commercial noise barriers;
 - 7.1.2.5 Shipping containers or buildings,
 - 7.1.2.6 A portable barrier such as a truck trailer equipped with movable flaps to block the space between the ground and the bottom of the trailer and increase height if required.
- 7.1.3 Noise barriers shielding portable equipment may be progressively established to provide shielding from location of operation to the identified noise sensitive point of reception (POR).

7.2 Mobile Screening Plant

- 7.2.1 The operation of the mobile screening plant (screener) shall take place only during the daytime period (07:00 to 19:00) and shall comply with the following:
 - 7.2.1.1 The screener is to be located on the pit floor at a maximum elevation of 188 mASL.
 - 7.2.1.2 Noise barriers are to be provided as per Table 7 and Figure 24.

7.3 Wash Plant

- 7.3.1 The operation of the wash plant and associated diesel generator shall take place only during the daytime period (07:00 to 19:00) and shall comply with the following:
 - 7.3.1.1 The wash plant is to be located on the pit floor at a maximum elevation of 188 mASL in locations shown in Figure 2.
 - 7.3.1.2 Noise barriers are to be provided as per Table 7 and Figure 25.
 - 7.3.1.3 The generator is to be housed inside a trailer and fitted with an exhaust silencer that meets the minimum insertion loss requirements listed in Table 8. The silencer is to be located inside the trailer or as close as possible to the location where the exhaust exits the trailer with the duct material between the silencer and the generator constructed of 16-gauge weather resistant metal. The silencers shall have a high transmission loss casing.
 - 7.3.1.4 Item 7.2.1.3 above does not apply if hydro is used to provide power to the plant.



7.4 Mobile Crushing Plant

- 7.4.1 The operation of the mobile crushing plant (crusher) shall take place only during the daytime period (07:00 to 19:00) and shall comply with the following:
- 7.4.1.1 The crusher is to be located on the pit floor at a maximum elevation of 188 mASL in locations shown in Figure 2.
 - 7.4.1.2 Noise barriers are to be provided as per Table 7 and Figure 26 and 27.

7.5 Loaders and Excavators

- 7.5.1 The operation of the loaders and excavators shall take place only during the daytime period (07:00 – 19:00), anywhere in the extraction area, and shall comply with the following:
- 7.5.1.1 A maximum of six (6) loaders or excavators may be in operation carrying out extraction, stockpiling and loading operations concurrently with other pit operations.

7.6 Highway Trucks


- 7.6.1 The loading and shipping of product using highway trucks shall take place only during the daytime period (07:00 – 19:00), and shall comply with the following:
- 7.6.1.1 When operating on-site, highway trucks shall not exceed 30 km/h and shall not use compression braking (Jake Brakes).

7.7 Portable construction equipment

- 7.7.1 Portable construction equipment used for site preparation (e.g. land clearing and construction of berms) and rehabilitation shall comply with MECP Publication NPC-115, Construction Equipment, August 1978. (This publication gives noise standards to be met by construction equipment in Ontario.) Site preparation and rehabilitation activities shall take place only during daytime hours (07:00 – 19:00).

7.8 New Process

- 7.8.1 If a new process is introduced to the site that is not currently included in the site plan, then this process shall be assessed by a qualified acoustical consultant prior to commissioning. Noise mitigation measures shall be reviewed, and altered, if necessary, to ensure that MECP sound level limits are met at all points of reception and the site plan shall be amended as required by the MNR.



8.0 Conclusions

An acoustic assessment of operations at the Proposed Highland Line Pit has been conducted according to MECP noise assessment procedures. Operations include extraction by loaders or excavators, aggregate processing operations by a mobile screening plant, a wash plant and a mobile crushing plant, loading processed sand and aggregate from stockpiles using loaders or excavators, and delivery and shipping of product using highway trucks.

It has been found that noise levels from the operations at nearby receptors are in compliance with MECP sound level limits as set out in publication NPC-300¹, provided that the noise mitigation measures described in Section 7.0 of this report are followed.



Professional Engineers 5th September 2025
Ontario

Limited Engineering Licensee


Name: M. A. WELLS

Number: 100542557

Limitations: Environmental acoustic assessments and recommendations to mitigate noise and vibration; acoustical engineering services for land-use planning, architectural and building acoustics, industrial acoustics, and occupational health and safety audits.


Association of Professional Engineers of Ontario

Michael Wells,
Limited Engineering Licensee, Professional Engineers Ontario, Registered Architect of NSW,
B. Architecture (Hons), B.Sc. Arch.,
Member, Canadian Acoustical Society, Member, Australian Acoustical Society (M.A.A.S.)



References

1. Ministry of Environment, Conservation and Parks Publication NPC-300, *Environmental Noise Guideline, Stationary and Transportation Sources – Approval and Planning*, August 2013, adopted by the MECP on 22 October 2013.
2. Ministry of Environment, Conservation and Parks, *Sample Application Package, Basic Comprehensive Certificate of Approval (Air and Noise)*, July 2009.
3. Ministry of Environment, Conservation and Parks Publication NPC-206, *Sound Levels due to Road Traffic*, October 1995.
4. Ministry of Environment, Conservation and Parks, Ontario Road Noise Analysis Method for Environment and Transportation (ORNAMENT), 1989.
5. Ministry of Environment, Conservation and Parks, STAMSON Software, Version 5.03, 1996. (Software implementation of reference 4).
6. International Standards Organization, *Acoustics - Attenuation of Sound during Propagation Outdoors, Part 2: General Method of Calculation*, ISO 9613-2: 1996(E).
7. Jade Acoustics, *Re: Acoustic Assessment Peer Review Highland Line Pit Part of Lot 5, Concession 10 Lanark Highland Township, Lanark County, Ontario, Pit Licence Number 626599, Our File: 25-016*, 14 April 2025.



TABLES

Table 1: Points of Reception Summary Table

Table 2: Noise Source Summary Table

Table 3: Exclusion Limit Values for One-Hour Equivalent
Sound Level (Leq, dBA) at Outdoor Points of Reception

Table 4: Exclusion Limit Values for One-Hour Equivalent Sound Level
(Leq, dBA) at Plane of Window of Noise Sensitive Spaces

Table 5: Applicable One Hour Sound Level Limits

Table 6: Acoustic Assessment Summary for Worst Case Operation

Table 7: Recommended Noise Barriers

Table 8: Minimum Insertion Loss for Generator Exhaust Silencer




Table 1: Point of Reception Summary Table*

Point of Reception	Location*
POR 1	Residence 626 Highland Line Road (2 storey)
POR 2	Hunting Camp 273 Leo Jay Road (1 storey)
POR 3	Residence 255 Leo Jay Road (2 storey)
POR 4	Residence 229 Leo Jay Road (1 storey) (also represents houses further east on Leo Jay Road)
POR 5	Residence 137 Anderson Lane (2 storey)
POR 6	Vacant Lot to the South via Concession Road 11 Dalhousie (2 storey)
POR 7	Wheelers Pancake House and Sugar Camp 1001 Highland Line Road (2 storey)
POR 8	Residence 1025 Highland Line Road (1.5 storey)
POR 9	Residence 804 Concession Road 11 Dalhousie (2 storey) (Also represents residence at 811 Concession Road 11)
POR 10	Residence 805 Concession Road 10 Dalhousie (2 storey) (Also represents residence at 811 Concession Road 11 Dalhousie)
POR 11	Residence 102 Camerons Road (2 storey)
POR 12	Vacant Lot 610 Highland Line Road (2 storey)
POR 13	Vacant Lot to the North Concession Road 11 Dalhousie (2 storey)

* For assessment purposes, points of reception, (POR), have been taken as upper floor windows (2 m above grade for single storey and 4.5 m above grade to represent two storey residences) and Outdoor Point of Reception (30 m from residence, 1.5 m above grade) in acoustic calculations. POR's located on vacant land have been assessed at 2 stories in height.




Table 2: Noise Source Summary Table

Source ID	Source Description	Sound Power (dBA)	Source Location Ht. above ground* (m)	Sound Characteristics	Noise Control Measures
Screener	Mobile Screening Plant	111.0	3.0	Steady, no significant tonality, non-directional	Refer Section 7.0
Wash Plant	Wash Plant	109.9	4.3	Steady, non-tonal, non-directional	As noted in section 7.0
Generator	Generator	108.5**	4	Steady, non-tonal, non-directional	As noted in section 7.0
Crusher	Mobile Crushing Plant	120.0	3.0	Steady, no significant tonality, non-directional	Refer Section 7.0
Loader_1 Loader_2 Loader_3	Loaders used for loading trucks or feeding the screener or crusher (CAT982M or similar)	103	2.5	Steady, moving, no significant tonality, non-directional	Refer Section 7.0
Excavator_1 Excavator_2 Excavator_3	Excavators for extraction or loading the screener or crusher (CAT345DL or similar)	103.2	2.5	Steady, moving, no significant tonality, non-directional	Refer Section 7.0
IHR_1 IHR_2	On-site truck movements for shipping	110.1	2.5	Steady, moving, no significant tonality, non-directional	Refer Section 7.0

*Height measured from finished grade at location of equipment operation.

**Includes attenuation provided by silencer as noted in Table 8.





Table 3: MECP Exclusion Limit Values for One-Hour Equivalent Sound Level (Leq, dBA) at Outdoor Points of Reception

Time of Day	Class 1 Area	Class 2 Area	Class 3 Area	Class 4 Area
07:00 – 19:00	50	50	45	55
19:00 – 23:00	50	45	40	55

Table 4: MECP Exclusion Limit Values for One-Hour Equivalent Sound Level (Leq, dBA) at Plane of Window of Noise Sensitive Spaces

Time of Day	Class 1 Area	Class 2 Area	Class 3 Area	Class 4 Area
07:00 – 19:00	50	50	45	60
19:00 – 23:00	50	50	40	60
23:00 – 07:00	45	45	40	55



**Table 5: Applicable One Hour Sound Level Limits for the Daytime Period
(07:00 – 19:00)**

Receptor & Point of Reception POW = Plane of Window OPR = Outdoor Point of Reception	Sound Level Limit 1-hour LAEQ dBA (Daytime Period, 07:00 – 19:00)	Sound Level Limit 1-hour LAEQ dBA (Evening Period, 19:00 – 23:00)	Sound Level Limit 1-hour LAEQ dBA (Nighttime Period, 23:00 – 07:00)
POR_1_POW	45	40	40
POR_1_OPR	45	40	-
POR_2_POW	45	40	40
POR_2_OPR	45	40	-
POR_3_POW	45	40	40
POR_3_OPR	45	40	-
POR_4_POW	45	40	40
POR_4_OPR	45	40	-
POR_5_POW	45	40	40
POR_5_OPR	45	40	-
POR_6_POW	45	40	40
POR_6_OPR	45	40	-
POR_7_POW	45	40	40
POR_7_OPR	45	40	-
POR_8_POW	45	40	40
POR_8_OPR	45	40	-
POR_9_POW	45	40	40
POR_9_OPR	45	40	-
POR_10_POW	45	40	40
POR_10_OPR	45	40	-
POR_11_POW	45	40	40
POR_11_OPR	45	40	-
POR_12_POW	45	40	40
POR_12_OPR	45	40	-
POR_13_POW	45	40	40
POR_13_OPR	45	40	-





Table 6.1: Acoustic Assessment Summary Table, Worst Case, Daytime Period of Operation, 7 am to 7 pm (07:00 - 19:00) – Before Mitigation

Point of Reception ID	Location	Scenario 1 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 2 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 3 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 4 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 5 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 6 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 7 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 8 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 9 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 10 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Performance Limit* Day-time Period (dBA)	Compliance with Performance Limit (Yes / No)
POR 1	POW	52	50.6	40.8	40.9	51.6	51.3	46.5	46.5	50.5	51.2	45	No
	OPR	51.4	49.2	40.1	40.2	51	50.5	46.5	46.5	49.5	50.5	45	No
POR 2	POW	44	44.2	39.5	39.4	44.8	44.8	42.1	42	44.2	44.8	45	Yes
	OPR	47.5	47.9	42.1	42.1	48.2	48.3	44.8	44.8	47.9	48.3	45	No
POR 3	POW	45.5	50.6	44.8	45	45.6	50	45	45	49.6	49.6	45	No
	OPR	42	46.6	37.8	37.7	42.1	46	38	38	45.5	45.6	45	No
POR 4	POW	44.7	50.1	40.5	40.5	44.8	49.5	40.5	40.5	49.3	49.3	45	No
	OPR	44.5	49.6	40.2	40.2	44.5	49	40.1	40.1	48.7	48.7	45	No
POR 5	POW	46.2	50.9	39.5	39.9	46.8	51.3	44.1	44.2	50.8	51.3	45	No
	OPR	42.8	49.3	42.9	43.3	42.9	49.3	43.4	43.5	49.2	49.2	45	No
POR 6	POW	30.5	28.6	37.7	38.1	31	30.6	38	38	30.2	31	45	Yes
	OPR	29.1	27.4	36.1	36.4	29.8	29.4	36.4	36.4	28.7	29.7	45	Yes
POR 7	POW	36.3	36.3	37.7	37.6	36.4	36.4	37.9	37.8	36.3	36.4	45	Yes
	OPR	30.5	29.8	34.2	34	30.9	30.7	34.5	34.4	30.6	30.9	45	Yes
POR 8	POW	41.4	41.6	46.5	46.5	41.5	41.5	46.5	46.4	41.4	41.5	45	No
	OPR	40.7	40.8	46.1	46.1	40.8	40.8	46.1	46.1	40.7	40.8	45	No
POR 9	POW	34.6	33.4	35.1	35.3	34.9	34.6	35.9	35.9	33.4	34.6	45	Yes
	OPR	33.5	32.5	34.6	34.5	33.9	33.6	35.1	35.1	32.5	33.6	45	Yes



Point of Reception ID	Location	Scenario 1 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 2 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 3 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 4 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 5 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 6 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 7 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 8 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 9 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 10 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Performance Limit* Day-time Period (dBA)	Compliance with Performance Limit (Yes / No)
POR 10	POW	26.5	16.9	0.8	0	27.2	25.9	25.4	25.4	18.1	26	45	Yes
	OPR	25.4	15.5	12.3	4.7	26.4	25.2	25	24.8	16.9	25.3	45	Yes
POR 11	POW	35.8	33.8	_ ^{**}	_ ^{**}	36.3	36	31.9	31.9	35.5	36.2	45	Yes
	OPR	33.9	33.4	_ ^{**}	_ ^{**}	34.1	34.1	27.5	27.5	33.8	34.2	45	Yes
POR 12	POW	47.2	44.2	42.5	42.1	47.9	47.2	46.5	46.4	46.3	47.7	45	No
	OPR	46.5	43.7	41.7	41.5	47.3	46.7	45.9	45.9	45.4	47	45	No
POR 13	POW	38.1	38.1	40.7	40.4	38.7	38.8	41	40.9	38	38.7	45	Yes
	OPR	37.2	37.3	40.1	39.7	37.6	37.7	40.2	40.1	37.2	37.6	45	Yes
POR 14	POW	26.3	19.6	_ ^{**}	_ ^{**}	27.8	26.9	26.1	26.1	27.8	28.1	45	Yes
	OPR	25.3	24.7	_ ^{**}	_ ^{**}	27.1	26.7	25.7	25.7	26.8	27.5	45	Yes
POR 15	POW	25.4	24.1	_ ^{**}	_ ^{**}	26.3	25.7	24.5	24.5	26.6	26.7	45	Yes
	OPR	26	24.8	_ ^{**}	_ ^{**}	27	26.8	25.4	25.4	26.8	27.4	45	Yes

*Performance limits are based on 1-hour equivalent sound levels, Leq.

**Noise impacts insignificant.





Table 6.2: Acoustic Assessment Summary Table, Worst Case, Daytime Period of Operation, 7 am to 7 pm (07:00 - 19:00) – After Mitigation

Point of Reception ID	Location	Scenario 1 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 2 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 3 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 4 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 5 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 6 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 7 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 8 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 9 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 10 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Performance Limit* Day-time Period (dBA)	Compliance with Performance Limit (Yes / No)
POR 1	POW	42.9	42.2	40.7	40.8	44	43.9	43.8	43.8	44.2	44.3	45	Yes
	OPR	41.7	39.5	39	39.1	43.2	42.9	43.1	43.2	43.1	43.5	45	Yes
POR 2	POW	39.9	40.4	39.4	39.4	40.5	40.7	40.9	40.9	40.4	40.6	45	Yes
	OPR	41.8	41.7	39	38.9	42.4	42.8	41.7	41.7	43.1	42.9	45	Yes
POR 3	POW	39.1	43.9	40.7	41.1	39.5	43.5	41	41.1	41.6	41.6	45	Yes
	OPR	34.3	40.3	37.7	37.7	34.4	39.5	37.7	37.7	37.5	37.4	45	Yes
POR 4	POW	37.2	42.7	40.4	40.5	37.5	41.9	40.4	40.4	40.3	40.3	45	Yes
	OPR	36.9	42.7	40.1	40.1	36.7	41.8	40	40	39.8	39.8	45	Yes
POR 5	POW	43.8	41.9	36.7	37.5	44	42.9	40.7	40.7	43.1	43.9	45	Yes
	OPR	40.5	40.8	38.3	39.2	40.5	40.4	39	39.3	41.4	41.4	45	Yes
POR 6	POW	30.5	28.4	37.7	38.1	31	30.5	38	38	30.1	31	45	Yes
	OPR	29.1	27.3	36.1	36.4	29.6	29.2	36.3	36.4	28.6	29.6	45	Yes
POR 7	POW	36.3	36.3	37.7	37.6	36.4	36.4	37.9	37.8	36.3	36.4	45	Yes
	OPR	30.5	29.8	34.2	34	30.9	30.7	34.5	34.4	30.6	30.9	45	Yes
POR 8	POW	41.3	41.5	44.3	44.3	41.4	41.5	44.3	44.3	41.4	41.4	45	Yes
	OPR	40.6	40.7	42.9	42.9	40.7	40.8	42.9	42.9	40.7	40.8	45	Yes
POR 9	POW	34	33.4	35.1	35.3	34.2	34	35.5	35.5	33.4	34	45	Yes
	OPR	33.1	32.5	34.6	34.5	33.3	33.1	34.7	34.7	32.5	33.1	45	Yes



Point of Reception ID	Location	Scenario 1 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 2 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 3 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 4 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 5 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 6 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 7 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 8 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 9 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Scenario 10 Estimated Sound Level Daytime Period (Worst Case) (dBA)	Performance Limit* Day-time Period (dBA)	Compliance with Performance Limit (Yes / No)
POR 10	POW	26	16.9	0.8	0	27	25.9	25.4	25.4	18.1	26	45	Yes
	OPR	24.7	15.5	12.3	4.7	26.2	25.2	25	24.8	16.8	25.3	45	Yes
POR 11	POW	32.1	30.2	_ ^{**}	_ ^{**}	32.6	32.2	28.1	28.1	32.2	32.7	45	Yes
	OPR	31.2	30.8	_ ^{**}	_ ^{**}	31.9	32	27.5	27.5	31.6	32.2	45	Yes
POR 12	POW	41.9	40.8	42.5	42.1	43.3	43.1	44.3	44.2	42	43.4	45	Yes
	OPR	41.1	40	41.7	41.5	43.1	42.9	44	43.9	41.3	43.1	45	Yes
POR 13	POW	38.1	38.1	40.7	40.4	38.2	38.2	40.7	40.6	38	38.2	45	Yes
	OPR	37.2	37.3	40.1	39.7	37.4	37.5	40	39.9	37.2	37.4	45	Yes
POR 14	POW	26.6	19.2	_ ^{**}	_ ^{**}	27.3	26.3	25.5	25.5	27.8	27.7	45	Yes
	OPR	25.5	24.5	_ ^{**}	_ ^{**}	26.7	26.2	25	25	26.8	27	45	Yes
POR 15	POW	25.3	23.8	_ ^{**}	_ ^{**}	26.1	25.4	24.3	24.3	26.6	26.6	45	Yes
	OPR	25.9	24.5	_ ^{**}	_ ^{**}	26.8	26.4	25	25	26.8	27.1	45	Yes

*Performance limits are based on 1-hour equivalent sound levels, Leq.

**Noise impacts insignificant.





Table 7: Recommended Noise Barriers

Barrier	Minimum Height (m / mASL)	Minimum Length (m)	Maximum Distance from Source (m)	Location	Required to shield Line of Sight from Identified Source ID	Required to shield Line of Sight to Identified Receptor/s	Description
Barrier_1 (Site berm)	196 mASL	Up to 100 m	-	As per: Figure 25	Mobile Screening Plant and extraction operations occurring in Extraction Area 1 East of Line AA	POR_12*	New barrier (berm / lift face): Required to shield noise impacts to the identified receptors when operating in Extraction Area 1 East of Line AA (Only required following development of a new noise sensitive development at POR 12)
Barrier_2 (Site berm)	196 mASL	Up to 400 m	-	As per: Figure 25	Mobile Screening Plant and extraction operations occurring in Extraction Area 1 East of Line AA	POR_1 POR_2 POR_3 POR_4	New barrier (berm / lift face): Required to shield noise impacts to the identified receptors when operating in Extraction Area 1 East of Line AA
Barrier_3 (Site berm)	3 m	Up to 285 m	-	As per: Figure 25	Mobile Screening Plant and extraction operations occurring in Extraction Area 1 South of Line BB	POR_5	New barrier (berm): Required to shield noise impacts at the identified receptor when operating in Extraction Area 1 South of Line BB
Barrier_SP1 (Stockpile)	4 m	10 m	20 m	As per: Figure 26	Screener when operating in Extraction Area 1	POR_5	New barrier (stockpile): Required to be maintained to shield noise impacts at the identified receptors when operating greater than 20 m from a lift face or site berm that otherwise shields in the direction of the identified receptors
Barrier_WP1 (Stockpile)	7 m	20 m	25 m	As per: Figure 27	Wash Plant and associated generator when operating in Extraction Area 1	POR_2	New barrier (stockpile): Required to be maintained to shield noise impacts at the identified receptor



Barrier	Minimum Height (m / mASL)	Minimum Length (m)	Maximum Distance from Source (m)	Location	Required to shield Line of Sight from Identified Source ID	Required to shield Line of Sight to Identified Receptor/s	Description
Barrier_WP2 (Stockpile)	6 m	30 m	25 m	As per: Figure 27	Wash Plant and associated generator when operating in Extraction Area 1	POR_5	New barrier (stockpile): Required to be maintained to shield noise impacts at the identified receptor
Barrier_CP1 (Stockpile)	10 m	47 m (55 m)*	20 m	As per: Figure 28	Crusher when operating in Extraction Area 1	POR_1 POR_2 POR_3 POR_5 POR_12*	New barrier (stockpile): Required to be maintained to shield noise impacts at the identified receptor. Required to be extended to minimum 55 m in length following development of a new noise sensitive development at POR 12.
Barrier_CP2 (Stockpile)	6 m	20 m	25 m	As per: Figure 29	Crusher when operating in Extraction Area 2	POR_8	New barrier (stockpile): Required to be maintained to shield noise impacts at the identified receptor
Barrier_CP3 (Stockpile)	6 m	30 m	25 m	As per: Figure 29	Crusher when operating in Extraction Area 2	POR_1 POR_2 POR_3 POR_4 POR_5	New barrier (stockpile): Required to be maintained to shield noise impacts at the identified receptor

*Shielding of receptors representing vacant lots only required following development of a new noise sensitive development.





Table 8: Minimum Insertion Loss for Generator Exhaust Silencer

Name	Octave Band Centre Frequency, Hz Minimum Dynamic Insertion Loss (dB)								Rw
	63	125	250	500	1000	2000	4000	8000	
Silencer to be installed at the generator exhaust ² (Source: Generator)	10	30	38	30	25	20	20	20	24


Notes:

1. Octave Band Centre Frequency, Hz, with minimum dynamic insertion loss in dB or dBA units re 10-12 Watts. Alternative levels at each frequency band permissible providing the overall insertion loss meets the overall insertion loss (Rw) as noted above and is not tonal in character.
2. Insertion loss based on Silex Silencer Model JB 6. Refer manufacturers data Appendix 4.



FIGURES

- Figure 1: Scaled Area Location Plan showing Receptor Locations
- Figure 2: Detail Site Layout & Surface Elevation Contours (elevation contours based on Land Information Ontario (LIO), Provincial Digital Elevation Model, at 2-meter intervals)
- Figure 3: Scenario 1: Worst Case, **Extraction Area 1** – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only)
- Figure 4: Prediction Results, Scenario 1: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 5: Scenario 2: Worst Case, **Extraction Area 1** - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 5 – (Day only)
- Figure 6: Prediction Results, Scenario 2: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 7: Scenario 3: Worst Case, **Extraction Area 2** - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 6 & 7 – (Day only)
- Figure 8: Prediction Results, Scenario 3: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 9: Scenario 4: Worst Case, **Extraction Area 2** - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only)
- Figure 10: Prediction Results, Scenario 4: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 11: Scenario 5: Worst Case, **Extraction Area 1** – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only)
- Figure 12: Prediction Results, Scenario 5: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 13: Scenario 6: Worst Case, **Extraction Area 1** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 5 – (Day only)
- Figure 14: Prediction Results, Scenario 6: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 15: Scenario 7: Worst Case, **Extraction Area 2** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 6 & 7 – (Day only)
- Figure 16: Prediction Results, Scenario 7: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 17: Scenario 8: Worst Case, **Extraction Area 2** - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only)



- Figure 18: Prediction Results, Scenario 8: Worst Case, Day Only– Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 19: Scenario 9 Worst Case, **Extraction Area 1** – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only)
- Figure 20: Prediction Results, Scenario 9: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 21: Scenario 10: Worst Case, **Extraction Area 1** – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only)
- Figure 22: Prediction Results, Scenario 10: Worst Case, Day Only – Noise Contours, (Noise levels at 4.5 m) – After Mitigation
- Figure 23: Detail site plan showing location of site berms and barrier requirements
- Figure 24: Detail plan at Mobile Screening Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 1**
- Figure 25: Detail plan at Wash Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 1**
- Figure 26: Detail plan at Mobile Crushing Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 1**
- Figure 27: Detail plan at Mobile Crushing Plant showing location of noise barriers (stockpiles) when operation in **Extraction Area 2**




Figure 1: Scaled Area Location Plan showing Receptor Locations





Figure 2: Detail Site Layout & Surface Elevation Contours (elevation contours based on Land Information Ontario (LIO), Provincial Digital Elevation Model, at 2-meter intervals)




Figure 3: Scenario 1: Worst Case, Extraction Area 1 – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only)




Figure 4: Prediction Results, Scenario 1 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation




Figure 5: Scenario 2: Worst Case, Extraction Area 1 - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 5 – (Day only)




Figure 6: Prediction Results, Scenario 2 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation





Figure 7: Scenario 3: Worst Case, Extraction Area 2 - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 6 & 7 – (Day only)





Figure 8: Prediction Results, Scenario 3 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation




Figure 9: Scenario 4: Worst Case, Extraction Area 2 - Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only)




Figure 10: Prediction Results, Scenario 4 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation




Figure 11: Scenario 5: Worst Case, Extraction Area 1 – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 1 & 12 (Day only)




Figure 12: Prediction Results, Scenario 5 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation





Figure 13: Scenario 6: Worst Case, Extraction Area 1 - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 5 – (Day only)




Figure 14: Prediction Results, Scenario 6 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation




Figure 15: Scenario 7: Worst Case, Extraction Area 2 - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 6 & 7 – (Day only)




Figure 16: Prediction Results, Scenario 7 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation





Figure 17: Scenario 8: Worst Case, Extraction Area 2 - Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 8 & 13 (Day only)




Figure 18: Prediction Results, Scenario 8 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation




Figure 19: Scenario 9: Worst Case, Extraction Area 1 – Crushing Plant and Screening Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only)




Figure 20: Prediction Results, Scenario 9 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation





Figure 21: Scenario 10: Worst Case, Extraction Area 1 – Crushing Plant and Wash Plant in operation concurrently with extraction occurring closest to POR 2, 3, 4, 14 & 15 (Day only)




Figure 22: Prediction Results, Scenario 10 - Day only (07:00 to 19:00): Noise Contours, (Noise levels at 4.5 m) – After Mitigation




Figure 23: Detail site plan showing location of site berms and barrier requirements




Figure 24: Detail plan at Mobile Screening Plant showing location of noise barriers (stockpiles) when operating in Extraction Area 1




Figure 25: Detail plan at Wash Plant showing location of noise barriers (stockpiles) when operation in Extraction Area 1




Figure 26: Detail plan at Mobile Crushing Plant showing location of noise barrier (stockpile) when operating in Extraction Area 1







Figure 27: Detail plan at Mobile Crushing Plant showing location of noise barriers (stockpiles) when operation in Extraction Area 2



Appendix 1


Zoning Plan and Land Use Designations

Contents:


- **Zoning Map:** Zoning By-law for the Township of Lanark Highlands, Dalhousie and North Sherbrooke, Schedule A2, By-law no. 2003-451 (source: Township of Lanark Highlands)

Legend:

Legend	
Zones	
Rural	RU
Residential Low Density	R1
Multiple Residential	R2
Hamlet	H
Limited Services Rural	LSR
Lakefront Development	LD
General Commercial	GC
Commercial Industrial	CM
Commercial Recreational	CR
Rural Industrial	MR
Waste Management Facility	WMF
-Licensed Area	WMF
-500m Influence Area	WMF
Mineral Aggregate Resources Pit	MXP
Mineral Aggregate Resources Quarry	MXQ
Mineral Aggregate Resources Reserve	MAR
Mining	MIN
Note: All Islands are zoned LD unless specifically shown otherwise.	
Note: Zones with an 'H' following the zone symbol e.g. MARH, illustrate properties which have been placed in a holding zone.	
Environmental Protection	
Organic Soils	
Regulated Flood Plain	(Zone) EP
Note: The flood plain elevation for the Mississippi River from Dalhousie Lake to Sheriden Rapids is available from the Mississippi Valley Conservation Authority	
Natural Heritage Features	
Fish Habitat	F
Cold Water Fishery (CWF)	
Deer Yards	
Bird Nesting Sites	
Wildlife Habitat	
ANSI's (Individually Zoned)	
Provincially Significant Wetlands	(Zone) EP
Locally Significant Wetlands	(Zone) EP
Ontario's Living Legacy Area	(Zone) EP
Mississippi River Corridor	M



Zoning Map: Zoning By-law for the Township of Lanark Highlands, Dalhousie and North Sherbrooke, Schedule A2,
By-law no. 2003-451 (source: Township of Lanark Highlands)



Appendix 2

Acoustic Modelling Details

Modeling Notes:

1. Acoustic model developed uses Cadna-A software, Version 2025.
2. Sound propagation is modeled according to ISO 9613-2: 1996(E).
3. The whole of the extraction area is modelled with an absorption coefficient of 0.35 representative of exposed earth. Barbers Lake has been modelled as 100% reflective with an absorption coefficient of 0.0. The surrounding area is modeled with an absorption coefficient of 1.0 indicative of a Class 3 Area.
4. MECP favoured conservative modelling assumptions are used, that is, 'no subtraction of negative ground attenuation' and 'no negative path differences'.

Contents:

Table A2.1	Point of Reception Location Table
Table A2.2	Point Sources
Table A2.3	Line Sources
Table A2.4	Noise Barriers
Table A2.5	Noise Source Library
Table A2.6	Noise Measurement Data
Table A2.7.1	Point of Reception Impacts by Source for Scenario 1 – After Mitigation
Table A2.7.2	Point of Reception Impacts by Source for Scenario 2 – After Mitigation
Table A2.7.3	Point of Reception Impacts by Source for Scenario 3 – After Mitigation
Table A2.7.4	Point of Reception Impacts by Source for Scenario 4 – After Mitigation
Table A2.7.5	Point of Reception Impacts by Source for Scenario 5 – After Mitigation
Table A2.7.6	Point of Reception Impacts by Source for Scenario 6 – After Mitigation
Table A2.7.7	Point of Reception Impacts by Source for Scenario 7 – After Mitigation
Table A2.7.8	Point of Reception Impacts by Source for Scenario 8 – After Mitigation
Table A2.7.9	Point of Reception Impacts by Source for Scenario 9 – After Mitigation
Table A2.7.10	Point of Reception Impacts by Source for Scenario 10 – After Mitigation
Table A2.8	Distance Source to Point of Reception
Table A2.9	Sample Calculation




Table A2.1 Point of Reception Location Table

Name	ID	Height	Coordinates		
			X	Y	Z
		(m)	(m)	(m)	(m)
POR_1_POW	POR_1_POW	4.5	18379580.1	4977742.32	196.59
POR_1_OPR	POR_1_OPR	1.5	18379571.9	4977715.22	193.5
POR_2_POW	POR_2_POW	2	18379839.3	4977415.89	202.34
POR_2_OPR	POR_2_OPR	1.5	18379817.4	4977394.72	203.42
POR_3_POW	POR_3_POW	4.5	18379984.5	4977371.54	202.5
POR_3_OPR	POR_3_OPR	1.5	18379954.5	4977361.94	193.41
POR_4_POW	POR_4_POW	2	18380064.5	4977342.74	192.17
POR_4_OPR	POR_4_OPR	1.5	18380034.5	4977342.74	191.8
POR_5_POW	POR_5_POW	4.5	18379735.4	4976850.07	202.5
POR_5_OPR	POR_5_OPR	1.5	18379716.7	4976867.27	197.47
POR_6_POW	POR_6_POW	4.5	18379565.3	4975904.68	208.47
POR_6_OPR	POR_6_OPR	1.5	18379543.8	4975924.38	207.99
POR_7_POW	POR_7_POW	4.5	18378464.3	4975991.28	212.5
POR_7_OPR	POR_7_OPR	1.5	18378485.6	4976005.73	210.11
POR_8_POW	POR_8_POW	3	18378286.9	4976586.73	217
POR_8_OPR	POR_8_OPR	1.5	18378316.9	4976586.73	215.5
POR_9_POW	POR_9_POW	4.5	18377685.2	4978067.51	211.83
POR_9_OPR	POR_9_OPR	1.5	18377708.6	4978043.38	206.85
POR_10_POW	POR_10_POW	4.5	18378180.5	4978781.85	211.92
POR_10_OPR	POR_10_OPR	1.5	18378199.5	4978759.04	208.56
POR_11_POW	POR_11_POW	4.5	18379217.5	4978949.27	209.33
POR_11_OPR	POR_11_OPR	1.5	18379217.5	4978919.27	204.61
POR_12_POW	POR_12_POW	4.5	18379123.8	4977813.76	203.62
POR_12_OPR	POR_12_OPR	1.5	18379123.8	4977783.76	199.57
POR_13_POW	POR_13_POW	4.5	18378013.4	4977492.92	195.23
POR_13_OPR	POR_13_OPR	1.5	18378032.9	4977470.48	191.45
POR_14_POW	POR_14_POW	4.5	18381431.4	4977300.6	189.44
POR_14_OPR	POR_14_OPR	1.5	18381399.4	4977298.6	186.14
POR_15_POW	POR_15_POW	4.5	18381407.9	4977124.18	188.82
POR_15_OPR	POR_15_OPR	1.5	18381380.8	4977137.46	185.2





Table A2.2 Point Sources

ID	Result. PWL			Lw / Li	Noise Source Library File	Operating Time			Direct.	Attenuation	Height	Coordinates		
	Day	Evening	Night	Type	Value	Day	Evening	Night				X	Y	Z
	(dBA)	(dBA)	(dBA)			(min/hr)	(min/hr)	(min/hr)			(m)	(m)	(m)	(m)
Crusher_S1_2_5_6	120	120	120	Lw	Crusher_KPI_JCI	60	0	0	(none)		3	18379309.54	4976978.97	191
Crusher_S3_4_7_8	120	120	120	Lw	Crusher_KPI_JCI	60	0	0	(none)		3	18378937.53	4976831.94	191
Crusher_S10_11	120	120	120	Lw	Crusher_KPI_JCI	60	0	0	(none)		3	18379309.54	4976978.97	191
Screener_S1	111	111	111	Lw	Powerscreen_Chiefton_1700	60	0	0	(none)		3	18379519.24	4977502.51	191
Screener_S2	111	111	111	Lw	Powerscreen_Chiefton_1700	60	0	0	(none)		3	18379453.94	4976961.84	191
Screener_S3	111	111	111	Lw	Powerscreen_Chiefton_1700	60	0	0	(none)		3	18378838.02	4976430.73	191
Screener_S4	111	111	111	Lw	Powerscreen_Chiefton_1700	60	0	0	(none)		3	18378640.03	4976699.08	191
Screener_S10	111	111	111	Lw	Powerscreen_Chiefton_1700	60	0	0	(none)		3	18379651.64	4977360.53	191
Washplant	109.9	109.9	109.9	Lw	Washplant	60	0	0	(none)		4.3	18379523	4977422	192.3
Generator	107.4	107.4	107.4	Lw	Generator_600kW	60	0	0	Chimney (VDI 3733 (1996))	Silex_Silencer_Model_J B 6	4	18379524.5	4977423.15	192
Excavator_1_S1_2_5_6	103.2	103.2	103.2	Lw	Excavator	60	60	60	(none)		2.5	18379355.25	4976985.73	190.5
Excavator_1_S3_4_7_8_9	103.2	103.2	103.2	Lw	Excavator	60	60	60	(none)		2.5	18378919.39	4976875.07	190.5
Excavator_1_S10_11	103.2	103.2	103.2	Lw	Excavator	60	60	60	(none)		2.5	18379355.25	4976985.73	190.5
Excavator_2_S1_5	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18379546.79	4977495.21	190.5
Excavator_2_S2_6	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18379491.02	4976980.28	190.5
Excavator_2_S3_7	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18378796.71	4976458.1	200.5
Excavator_2_S4_8_9	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18378608.55	4976679.46	200.5
Excavator_2_S10_11	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18379682.82	4977358.58	190.5
Excavator_3_S1_5_9	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18379515.95	4977496.51	190.5
Excavator_3_S2_6	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18379416.12	4976935.86	190.5
Excavator_3_S3_7	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18378819.42	4976497.67	190.5
Excavator_3_S4_8	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18378664.54	4976674.71	190.5
Excavator_3_S10_11	103.2	103.2	103.2	Lw	Excavator	60	0	0	(none)		2.5	18379656.42	4977365.67	190.5



ID	Result. PWL			Lw / Li	Noise Source Library File	Operating Time			Direct.	Attenuation	Height	Coordinates		
	Day	Evening	Night	Type	Value	Day	Evening	Night				X	Y	Z
	(dBA)	(dBA)	(dBA)			(min/hr)	(min/hr)	(min/hr)			(m)	(m)	(m)	(m)
Loader_1__S1_2_5_6_9	103	103	103	Lw	Loader	60	60	60	(none)		2.5	18379299.24	4976986.65	190.5
Loader_1_S3_4_7_8	103	103	103	Lw	Loader	60	60	60	(none)		2.5	18378905.23	4976851.35	190.5
Loader_1__S10_11	103	103	103	Lw	Loader	60	60	60	(none)		2.5	18379299.24	4976986.65	190.5
Loader_2_S1_5	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379508.72	4977507.08	190.5
Loader_2_S2_6	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379434.91	4976952.97	190.5
Loader_2_S3_7	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18378880.45	4976492.73	190.5
Loader_2_S4_8_9	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18378612.65	4976723.09	190.5
Loader_2_S9	103	103	103	Lw	Loader				(none)		2.5	18378612.65	4976723.09	190.5
Loader_2_S10_11	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379644.75	4977370.45	190.5
Loader_3_S1	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379493.51	4977492.14	190.5
Loader_3_S2	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379434	4976942.1	190.5
Loader_3_S3	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18378890.39	4976461.66	190.5
Loader_3_S4	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18378594.36	4976697.66	200.5
Loader_3_S5_6_7_8_9	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379513.6	4977422.68	190.5
Loader_3_S9	103	103	103	Lw	Loader				(none)		2.5	18379513.6	4977422.68	190.5
Loader_3_S10	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379629.55	4977355.51	190.5
Loader_3_S11	103	103	103	Lw	Loader	60	0	0	(none)		2.5	18379513.6	4977422.68	190.5




Table A2.3 Line Sources

ID	Result. PWL			Lw / Li	Noise Source Library File	Direct.	Moving Pt. Src			
	Day	Evening	Night	Type	Value		Number			Speed
	(dBA)	(dBA)	(dBA)				Day	Evening	Night	(km/h)
IHR_1_S1	107.9	103.1	103.1	PWL-Pt	HWYTruck_Slow58	(none)	15	5	5	30
IHR_1_S2	108.4	103.6	103.6	PWL-Pt	HWYTruck_Slow58	(none)	15	5	5	30
IHR_1_S5	107.6	102.9	102.9	PWL-Pt	HWYTruck_Slow58	(none)	15	5	5	30
IHR_1_S6	108.6	103.8	103.8	PWL-Pt	HWYTruck_Slow58	(none)	15	5	5	30
IHR_1_S7_8	100.5	100.5	100.5	PWL-Pt	HWYTruck_Slow58	(none)	5	5	5	30
IHR_1_S9	103.1	103.1	103.1	PWL-Pt	HWYTruck_Slow58	(none)	5	5	5	30
IHR_2_S3_7	105	105	105	PWL-Pt	HWYTruck_Slow58	(none)	10	10	10	30
IHR_2_S4_8	104.1	104.1	104.1	PWL-Pt	HWYTruck_Slow58	(none)	10	10	10	30
IHR_2_S9	104.1	104.1	104.1	PWL-Pt	HWYTruck_Slow58	(none)	10	10	10	30
IHR_1_S10	108.3	103.5	103.5	PWL-Pt	HWYTruck_Slow58	(none)	15	5	5	30
IHR_1_S11	108.4	103.6	103.6	PWL-Pt	HWYTruck_Slow58	(none)	15	5	5	30




Table A2.4 Noise Barriers

ID	Height
	(m)
Barrier_1	196 mASL
Barrier_2	196 mASL
Barrier_3	3
Barrier_SP1	4
Barrier_SP1	4
Barrier_SP1	4
Barrier_CP1	10
Barrier_CP2	6
Barrier_CP3	6
Barrier_WP1	7
Barrier_WP2	6




Table A2.5 Noise Source Library

ID	Type	Spectra (dB)									A	lin	Source
		31.5	63	125	250	500	1000	2000	4000	8000			
Powerscreen_Chiefton_1700	Lw	106.9	110.7	112.9	110.6	104.8	105.2	104.9	101	92	111	117.7	Measured 21 Oct 2019, Cavanaugh Pine Grove Pit
Washplant	Lw	112.8	116.6	117.9	105.6	103.6	104	103.3	99.9	88.2	109.9	121.4	Measured Lanark Quarry 14 Oct 2020 72 at 73 m
Generator_600kW	Lw	65	97.5	112.6	120.3	121.9	123	125	121.2	109.4	129.7	134.2	Manufacturers Data - Cummins600DQPAA-Open Exhaust
Crusher_KPI_JCI	Lw	115.5	123.3	122.3	118.8	114.9	116.5	111.7	105.9	96.4	120	127.7	Measured 18 March 2019, KNL Construction Site
Loader	Lw	107.3	109.5	107.1	101.8	99.4	97.6	95.9	90.1	82.9	103	113.6	Meas. Howe-Ross Pit 20-05-13 72dBA at 14m
Excavator	Lw	100	110.2	109	100.8	98.5	98	95.2	92.6	87.7	103.2	113.5	Meas. OTR 23rd August 2017 at 13.0m
HWYTruck_Slow58	Lw	115.9	112.7	110.2	101.6	101.4	105	104.2	97.6	103.5	110.1	119	Brockville McDowell Study, 2003

Table A2.6 Noise Measurement Data

ID	Type	Spectra (dB)									A	lin	Source*
		31.5	63	125	250	500	1000	2000	4000	8000			
Meas_Washplant	Li	74.9	78.7	80	67.7	65.7	66.1	65.4	62	50.3	72	83.5	Measured Lanark Quarry 14 Oct 2020 72 at 73 m
Meas_Powerscreen_Chiefton_1700	Li	66.2	70	72.2	69.9	64.1	64.5	64.2	60.3	51.3	70.3	77	Measured 21 Oct 2019, Cavanaugh Pine Grove Pit
Meas_Crusher_KPI_JCI	Li	67.3	77	71.3	72.5	65.4	70	65.1	57.7	48.1	72.9	80.2	Measured 18 March 2019, KNL Construction Site@50m
Meas Loader	Li	76.3	78.5	76.1	70.8	68.4	66.6	64.9	59.1	51.9	72	82.6	Meas. Howe-Ross Pit 20-05-13 72dBA at 14m
Meas_Excavator_CAT345DL	Li	69.6	79.8	78.6	70.4	68.1	67.6	64.8	62.2	57.3	72.8	83.1	Meas. OTR 23rd August 2017 at 13.0m
Meas_HWYTruck_Slow58	Li	67.5	64.3	61.8	53.2	53	56.6	55.8	49.2	55.1	61.7	70.6	adj. 90m source Brockville McDowell Study, 2003




Table A2.7.1 Point of Reception Impacts by Source for Scenario 1* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S1_2_ 5 6	38	31. 9	36. 5	36. 7	34. 3	31. 6	33. 8	33. 5	40	38. 8	27. 1	26	35. 6	29. 2	40. 9	40. 3	33. 1	32. 1			29	28. 7	38. 1	37	37. 3	36. 5				
IHR_1_ S1	36. 4	36. 4	30. 1	34. 5	35. 1	26. 1	33. 6	33. 4	36. 1	31. 3	20. 2	18. 8	19. 2	14. 9	20. 3	19. 6	17. 9	17. 3	17. 5	16	20	19	31. 7	31. 2	20. 4	19. 8	17. 7	16. 8	17	17.2
Screene r S1	35. 6	35. 9	33. 1	35. 3	29. 2	24. 2	21. 8	20. 5	35. 7	29. 5	24	22. 2	22. 6	20. 4	26. 3	25. 3	22. 9	21. 6	23. 1	21. 7	25. 9	24. 7	36. 1	35. 2	26	24. 7	23. 3	21. 9	21. 8	22.5
Loader_ 3 S1	33. 3	32. 9	26. 6	28. 8	22. 2	18. 1	15. 9	14. 8	32. 3	24. 8	17. 4	15. 9	16. 1	13. 8	19	18. 5	15. 4	14. 6	13. 6	12. 7	18. 3	14. 1	25. 7	25. 5	18. 2	17. 4	17	16. 2	15. 2	15.6
Loader_ 2 S1 5	29. 9	30. 2	25. 7	28. 3	22. 4	18. 4	16. 1	15	32. 2	25. 1	17. 3	15. 8	16	13. 8	19. 2	18. 6	15. 6	14. 8	14. 3	13. 3	18. 7	14. 8	26. 3	25. 9	18. 5	17. 6	16. 4	15. 5	15. 1	15.8
Excavat or_3_S1 5 9	29. 8	30. 2	27	29. 1	22. 8	18. 9	16. 6	15. 5	30. 1	24	17. 5	16. 1	16. 1	14. 3	19. 5	18. 9	16. 2	15. 3	16. 3	15. 5	19. 1	17. 2	28. 7	28. 3	19. 1	18. 3	17. 1	16. 4	15. 5	15.9
Excavat or_1_S1 2 5 6	27. 8	26. 7	26. 5	30. 1	27. 3	23. 2	21. 9	22. 2	21. 5	18. 7	5.7	5.3	19	13	15. 5	14. 8	16. 5	15. 8			16. 8	16	26. 3	25. 9	20. 4	19. 7				
Excavat or_2_S1 5	26. 4	27. 2	26	29. 3	22. 1	17. 8	15. 5	14. 8	32	25. 6	17. 5	16. 1	16. 1	14. 4	19. 4	18. 8	16. 5	15. 6	16. 2	15. 4	15. 9	14. 9	30. 3	30. 1	19. 5	18. 7	15. 9	14. 9	15. 5	16.2
Loader_ 1_S1_ 2 5 6 9	18. 9	14. 2	20. 2	20. 4	22	19. 5	18. 3	18	25	23. 8	12	11	18. 9	14	24	23. 2	16. 5	15. 6			16. 6	15. 8	26. 2	25. 7	20. 5	19. 7				
Total	42. 9	41. 7	39. 9	41. 8	39. 1	34. 3	37. 2	36. 9	43. 8	40. 5	30. 5	29. 1	36. 3	30. 5	41. 3	40. 6	34	33. 1	26	24. 7	32. 1	31. 2	41. 9	41. 1	38. 1	37. 2	26. 6	25. 5	25. 3	25.9

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.2 Point of Reception Impacts by Source for Scenario 2* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S1_2_5 6	38	31.9	36.5	36.7	38.2	35.5	37.8	37.5	37.2	36.7	27.1	26	35.6	29.2	40.9	40.3	33.1	32.1			29	28.7	38.1	37	37.3	36.5				
IHR_1_2 S2	36.4	36.3	30.7	35	37	29.4	35.2	34.2	37.2	34.2	20.2	18.7	19.7	14.4	22.1	21.5	18	17.6	16.9	15.5	20.1	19.3	31.4	30.8	21.4	20.9	18	15.4	17.3	18.1
Screener S2	34.9	31.5	34.3	34.5	36.9	34.3	36.4	37.1	32.7	33.1	13.9	13	23.7	14.2	29.7	27.3						22.2	32.8	32.3	26.4	25.4		22	20.9	20.8
Excavator_2 S2 6	28.1	24.6	27.9	31.6	34.9	31.2	29.7	29.8	23.2	24	6.3	5.8	18.5	11.4	22	19.2					16.7	16	25.8	25.4	19.5	18.7	12.9	12.5	10.3	11.3
Excavator_1 S1 2 5 6	27.8	26.7	26.5	30.1	32.4	28.8	32.4	31.8	32.1	31	11.7	10.9	19	13	15.5	14.8	16.5	15.8			16.8	16	26.3	25.9	20.4	19.7				
Loader_2 S2 6	27.7	24.7	27	27.2	29.4	26.7	28.9	29.4	26.2	26.4	8.3	8	14.8	7	22.1	17.9						15.7	25.8	25.3	19.7	18.9		15.8	14.7	14.8
Loader_3 S2	27.6	24.7	26.9	27.1	31	27.6	28.7	28.7	24.9	24.7	6.7	6.4	13.2	6.1	19.1	15						15.6	25.7	25.2	19.7	18.9		14.9	13.6	13.7
Excavator_3 S2 6	27.4	25	26.8	26.9	29	26.5	28.5	30	25.9	25.6	8.1	7.7	9.9	4.7	15.4	12.3						15.7	25.6	25.2	19.8	19.1				14.8
Loader_1 S1 2 5 6 9	18.9	14.2	20.2	20.4	22	19.5	21.6	21.4	23.1	22.3	12	11	18.9	14	24	23.2	16.5	15.6			16.6	15.8	26.2	25.7	20.5	19.7				
Total	42.2	39.5	40.4	41.7	43.9	40.3	42.7	42.7	41.9	40.8	28.4	27.3	36.3	29.8	41.5	40.7	33.4	32.5	16.9	15.5	30.2	30.8	40.8	40	38.1	37.3	19.2	24.5	23.8	24.5

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.3 Point of Reception Impacts by Source for Scenario 3* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S3_4_7_8	40.1	38.2	38.6	38.2	40	36.9	39.8	39.4	35.8	37.6	37.2	35.6	37.3	33.7	43.7	42.1	34.6	33.8					41.4	40.9	40	39.3				
Screener _S3	26.9	26	26.4	25.8	28.2	25.8	27.1	27	21.3	18.9	20.2	18.2	15.8	15.4	24	24		22.2					31.9	29.9	28.2	27.3				
Excavator_2 _S3_7	24.2	19.5	23.4	22.3	21.1	19.3	20.3	20.1	20.4	17	21.7	20	19.4	17.7	23.8	23.4	16.9	16.1					25.1	23.4	21.8	21.1				
Excavator_1 _S3_4_7_8_9	23.2	22.6	21.8	21.5	23	20.1	22.5	22.2	24.2	26.2	20.3	18.9	20.5	17.7	28.9	28.7	18.2	17.4					24.5	24	23.4	22.7				
Loader_1 _S3_4_7_8	23.2	22.6	21.5	21.2	22.8	19.9	22.3	22	22.2	21.7	20.3	18.8	20.4	17.1	29.3	28.9	18.2	17.4					24.6	24.1	23.4	22.8				
IHR_2_3 _S3_7	21.2	20.8	23.3	22.6	22.8	19.3	21.5	21.2	21.2	22	18.1	15.2	17.6	13.4	29	28.1	16.2	15.6	0.8	12.3			26.5	22.7	22	21.5				
Loader_2 _S3_7	20.7	19.9	20.1	19.6	21.9	19.7	21	20.7	14.8	16.9	14.6	13.1	16.8	15.2	25.4	24.5	16.6	15.8					25.6	23.7	21.5	20.7				
Excavator_3 _S3_7	20.5	19.8	19.9	19.5	21.3	19.6	20.7	20.5	18.8	17.6	18.9	16.9	12	11.4	21.3	20.7	17	16.2					25.4	23.8	21.8	21.1				
Loader_3 _S3	20.5	19.8	20	19.5	21.5	19.6	20.7	20.5	10.4	11.4	11.4	10.2	16.7	15.3	24.6	23.6		15.7					25.4	20.5	21.2	20.5				
Total	40.7	39	39.4	39	40.7	37.7	40.4	40.1	36.7	38.3	37.7	36.1	37.7	34.2	44.3	42.9	35.1	34.6	0.8	12.3	-80.2	-80.2	42.5	41.7	40.7	40.1	-80.2	-80.2	-80.2	-80.2

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.4 Point of Reception Impacts by Source for Scenario 4* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S3_4_ 7_8	40.1	38.2	38.6	38.2	40	36.9	39.8	39.4	35.8	37.6	37.2	35.6	37.3	33.7	43.7	42.1	34.6	33.8					41.4	40.9	40	39.3				
Screene r S4	27.6	26.7	26.1	25.5	31.5	24.7	26.9	26.6	28.3	30.2	26.6	24.7	15.6	11.6	27.7	27.7	20.7	20.3					29.2	28.3	20.6	20.1				
Excavat or_2_S4 8_9	24.4	22.8	22.9	21.8	24.3	21.1	24	23	21.6	23	20	18.6	11.9	9.2	23.4	23.8	18.5	17.8					26	24.4	21.3	20.8				
Loader_ 3 S4	24.4	22.4	22.7	21.5	24.3	20.8	23.7	22.6	21.7	22.8	19.8	18.3	11.3	8.5	23.7	23.9	16.9	15.9					22	21.3	18.3	17.9				
Excavat or_1_S3 _4_7_8_ 9	23.2	22.6	21.8	21.5	23	20.1	22.5	22.2	24.2	26.2	20.3	18.9	20.5	17.7	28.9	28.7	18.2	17.4					24.5	24	23.4	22.7				
Loader_ 1_S3_4 7_8	23.2	22.6	21.5	21.2	22.8	19.9	22.3	22	22.2	21.7	20.3	18.8	20.4	17.1	29.3	28.9	18.2	17.4					24.6	24.1	23.4	22.8				
Excavat or_3_S4 8	20.8	20.1	19.6	19.1	20.5	18.4	20.2	20	21.3	23.5	20.2	18.5	12.2	8.2	21.6	21.8	17.8	17					22.2	21.6	18.8	18.3				
IHR_2_ S4_8	20.3	19.9	19.1	18.6	23.9	17.6	20	19.7	22.1	23.9	18.1	16	16.4	12.1	28.8	28.2	15.5	15	0	4.7			21.9	21.6	20.4	19.3				
Loader_ 2_S4_8 9	19.4	19.8	19.2	18.6	24.5	17.9	19.7	19.4	21.6	23	19.7	18	7.8	5.6	19.9	20.3	5.8	5.8					13.7	13.9	8.6	8.7				
Total	40.8	39.1	39.4	38.9	41.1	37.7	40.5	40.1	37.5	39.2	38.1	36.4	37.6	34	44.3	42.9	35.3	34.5	0	4.7	-80.2	-80.2	42.1	41.5	40.4	39.7	-80.2	-80.2	-80.2	-80.2

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.5 Point of Reception Impacts by Source for Scenario 5* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1_ PO W	POR 1_ OPR	POR 2_ PO W	POR 2_ OPR	POR 3_ PO W	POR 3_ OPR	POR 4_ PO W	POR 4_ OPR	POR 5_ PO W	POR 5_ OPR	POR 6_ PO W	POR 6_ OPR	POR 7_ PO W	POR 7_ OPR	POR 8_ PO W	POR 8_ OPR	POR 9_ PO W	POR 9_ OPR	POR 10_ PO W	POR 10_ OP R	POR 11_ PO W	POR 11_ OP R	POR 12_ PO W	POR 12_ OP R	POR 13_ PO W	POR 13_ OP R	POR 14_ PO W	POR 14_ OP R	POR 15_ PO W	POR 15_ OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S1_2_ 5_6	38	31. 9	36. 5	36. 7	34. 3	31. 6	33. 8	33. 5	40	38. 8	27. 1	26	35. 6	29. 2	40. 9	40. 3	33. 1	32. 1			29	28. 7	38. 1	37	37. 3	36. 5				
Washpla nt	37. 7	37. 9	34. 2	36. 5	28. 3	23. 9	22. 4	22. 2	34. 9	28	24. 6	23. 2	23. 2	22. 1	26. 5	26	23. 1	22. 3	23. 3	22. 5	25. 9	25. 1	37	37. 2	26. 1	25. 3	23. 6	23. 2	22. 3	23.1
Generat or	36. 4	36. 6	29. 9	32. 6	23. 8	20. 3	18. 7	18. 6	33. 8	25	20. 4	18. 8	18. 6	17. 5	22. 7	22. 6	18. 5	18. 3	18. 7	18. 6	21. 9	21. 9	36. 3	36. 8	22. 3	22. 2	18. 5	18	17. 3	18.1
IHR_1_ S5	36. 3	36. 3	29. 9	33. 7	35. 9	26. 1	34. 2	32. 7	36	31. 5	20. 1	18. 6	19	14. 7	19. 9	19. 2	17. 7	17. 1	17. 3	15. 9	19. 6	18. 8	31. 6	31. 2	20. 1	19. 5	18	17. 1	16. 9	17.2
Loader_ 3_S5_6 7_8_9	30. 9	30. 7	25. 4	28. 2	19. 4	15. 7	13. 7	13. 4	27. 5	20. 3	17. 4	14	16. 4	14. 3	19. 9	19. 2	16. 7	15. 9	16. 9	16. 1	19. 4	18. 6	31. 1	30. 5	19. 8	19	16. 6	15. 7	15. 3	15.6
Loader_ 2_S1_5	29. 9	30. 2	25. 7	28. 3	22. 4	18. 4	16. 1	15	32. 2	25. 1	17. 3	15. 8	16	13. 8	19. 2	18. 6	15. 6	14. 8	14. 3	13. 3	18. 7	14. 8	26. 3	25. 9	18. 5	17. 6	16. 4	15. 5	15. 1	15.8
Excavat or_3_S1 5_9	29. 8	30. 2	27	29. 1	22. 8	18. 9	16. 6	15. 5	32. 2	25. 3	17. 5	16. 1	16. 1	14. 3	19. 5	18. 9	16. 2	15. 3	16. 3	15. 5	19. 1	17. 2	28. 7	28. 3	19. 1	18. 3	17. 1	16. 4	15. 5	15.9
Excavat or_1_S1 2_5_6	27. 8	26. 7	26. 5	30. 1	27. 3	23. 2	21. 9	22. 2	21. 5	18. 7	5.7	5.3	19	13	15. 5	14. 8	16. 5	15. 8			16. 8	16	26. 3	25. 9	20. 4	19. 7				
Excavat or_2_S1 5	26. 4	27. 2	26	29. 3	22. 1	17. 8	15. 5	14. 8	32	25. 6	17. 5	15. 7	16. 1	14. 4	19. 4	18. 8	16. 5	15. 6	16. 2	15. 4	15. 9	14. 9	30. 3	30. 1	19. 5	18. 7	15. 9	14. 9	15. 5	16.2
Loader_ 1_S1_ 2_5_6_9	18. 9	14. 2	20. 2	20. 4	22	19. 5	18. 3	18	25	23. 8	12	11	18. 9	14	24	23. 2	16. 5	15. 6			16. 6	15. 8	26. 2	25. 7	20. 5	19. 7				
Total	44	43. 2	40. 5	42. 4	39. 5	34. 4	37. 5	36. 7	44	40. 5	31	29. 6	36. 4	30. 9	41. 4	40. 7	34. 2	33. 3	27	26. 2	32. 6	31. 9	43. 3	43. 1	38. 2	37. 4	27. 3	26. 7	26. 1	26.8

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.6 Point of Reception Impacts by Source for Scenario 6* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S1_2_ 5 6	38	31.9	36.5	36.7	38.2	35.5	37.8	37.5	37.2	36.7	27.1	26	35.6	29.2	40.9	40.3	33.1	32.1			29	28.7	38.1	37	37.3	36.5				
Washpla nt	37.7	37.9	34.2	36.5	28.3	23.9	22.4	22.2	34.9	28	24.6	23.2	23.2	22.1	26.5	26	23.1	22.3	23.3	22.5	25.9	25.1	37	37.2	26.1	25.3	23.6	23.2	22.3	23.1
IHR_1_ S6	36.6	36.5	30.8	34.7	36.9	29.4	35.6	34.5	37.2	34.3	20.3	18.8	19.8	14.6	22.3	21.7	18.5	18	17.2	15.8	20.3	19.5	32.2	31.8	21.6	21	18	17.5	17.2	18
Generat or	36.4	36.6	29.9	32.6	23.8	20.3	18.7	18.6	33.8	25	20.4	18.8	18.6	17.5	22.7	22.6	18.5	18.3	18.7	18.6	21.9	21.9	36.3	36.8	22.3	22.2	18.5	18	17.3	18.1
Loader_ 3_S5_6 7 8 9	30.9	30.7	25.4	28.2	19.4	15.7	13.7	13.4	27.5	20.3	17.4	14	16.4	14.3	19.9	19.2	16.7	15.9	16.9	16.1	19.4	18.6	31.1	30.5	19.8	19	16.6	15.7	15.3	15.6
Excavat or_2_S2 6	28.1	24.6	27.9	31.6	34.9	31.2	29.7	29.8	23.2	24	6.3	5.8	18.5	11.4	22.5	21.8					16.7	16	25.8	25.4	19.5	18.7	12.9	12.5	10.3	11.3
Excavat or_1_S1 2 5 6	27.8	26.7	26.5	30.1	32.4	28.8	32.4	31.8	32.1	31	11.7	10.9	19	13	15.5	14.8	16.5	15.8			16.8	16	26.3	25.9	20.4	19.7				
Loader_ 2_S2_6	27.7	24.7	27	30.5	34.1	30	33.4	33.2	26.2	26.4	8.3	8	14.8	7	22.1	17.9						15.7	25.8	25.3	19.7	18.9		15.8	14.7	14.8
Excavat or_3_S2 6	27.4	25	26.8	30.4	33.6	29.9	28.5	32.8	25.9	25.6	8.1	7.7	9.9	4.7	15.4	12.3						15.7	25.6	25.2	19.8	19.1				14.8
Loader_ 1_S1_ 2 5 6 9	18.9	14.2	20.2	20.4	22	19.5	21.6	21.4	23.1	22.3	12	11	18.9	14	24	23.2	16.5	15.6			16.6	15.8	26.2	25.7	20.5	19.7				
Total	43.9	42.9	40.7	42.8	43.5	39.5	41.9	41.8	42.9	40.4	30.5	29.2	36.4	30.7	41.5	40.8	34	33.1	25.9	25.2	32.2	32	43.1	42.9	38.2	37.5	26.3	26.2	25.4	26.4

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.7 Point of Reception Impacts by Source for Scenario 7* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S3_4_ 7_8	40.1	38.2	38.6	38.2	40	36.9	39.8	39.4	35.8	37.6	37.2	35.6	37.3	33.7	43.7	42.1	34.6	33.8					41.4	40.9	40	39.3				
Washpla nt	37.7	37.9	34.2	36.5	28.3	23.9	22.4	22.2	34.9	28	24.6	23.2	23.2	22.1	26.5	26	23.1	22.3	23.3	22.5	25.9	25.1	37	37.2	26.1	25.3	23.6	23.2	22.3	23.1
Generat or	36.4	36.6	29.9	32.6	23.8	20.3	18.7	18.6	33.8	25	20.4	18.8	18.6	17.5	22.7	22.6	18.5	18.3	18.7	18.6	21.9	21.9	36.3	36.8	22.3	22.2	18.5	18	17.3	18.1
Loader_ 3_S5_6 7_8_9	30.9	30.7	25.4	28.2	19.4	15.7	13.7	13.4	27.5	20.3	17.4	14	16.4	14.7	19.9	19.2	16.7	15.9	16.9	16.1	19.4	18.6	31.1	30.5	19.8	19	16.6	15.7	15.3	15.6
IHR_1_ S7_8	30.6	30.7	22.9	26.3	26.7	16.4	23.7	22.4	30.1	24.7	12.7	11.3	10.3	7.3	13.4	12.8	10.9	10.3	10.2	9.7	12.8	11.9	25.9	25.5	14	13.5	10.3	9.9	11.6	12.1
Excavat or_2_S3 _7	24.2	19.5	23.4	22.3	21.1	19.3	20.3	20.1	20.4	17	21.7	20	19.4	17.7	23.8	23.4	16.9	16.1					25.1	23.4	21.8	21.1				
Excavat or_1_S3 _4_7_8_ _9	23.2	22.6	21.8	21.5	23	20.1	22.5	22.2	24.2	26.2	20.3	18.9	20.5	17.7	28.9	28.7	18.2	17.4					24.5	24	23.4	22.7				
Loader_ 1_S3_4 7_8	23.2	22.6	21.5	21.2	22.8	19.9	22.3	22	22.2	21.7	20.3	18.8	20.4	17.1	29.3	28.9	18.2	17.4					24.6	24.1	23.4	22.8				
IHR_2_ S3_7	21.2	20.8	23.3	22.6	22.8	19.3	21.5	21.2	21.2	22	18.1	15.2	17.6	13.4	29	28.1	16.2	15.6	0.8	12.3			26.5	22.7	22	21.5				
Loader_ 2_S3_7	20.7	19.9	20.1	19.6	21.9	19.7	21	20.7	14.8	16.9	14.6	13.1	16.8	15.2	25.4	24.5	16.6	15.8					25.6	23.7	21.5	20.7				
Excavat or_3_S3 _7	20.5	19.8	19.9	19.5	21.3	19.6	20.7	20.5	18.8	17.6	18.9	16.9	12	11.4	21.3	20.7	17	16.2					25.4	23.8	21.8	21.1				
Total	43.8	43.1	40.9	41.7	41	37.7	40.4	40	40.7	39	38	36.3	37.9	34.5	44.3	42.9	35.5	34.7	25.4	25	28.1	27.5	44.3	44	40.7	40	25.5	25	24.3	25

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.8 Point of Reception Impacts by Source for Scenario 8* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S3_4_ 7_8	40.1	38.2	38.6	38.2	40	36.9	39.8	39.4	35.8	37.6	37.2	35.6	37.3	33.7	43.7	42.1	34.6	33.8					41.4	40.9	40	39.3				
Washpl nt	37.7	37.9	34.2	36.5	28.3	23.9	22.4	22.2	34.9	28	24.6	23.2	23.2	22.1	26.5	26	23.1	22.3	23.3	22.5	25.9	25.1	37	37.2	26.1	25.3	23.6	23.2	22.3	23.1
Generat or	36.4	36.6	29.9	32.6	23.8	20.3	18.7	18.6	33.8	25	20.4	18.8	18.6	17.5	22.7	22.6	18.5	18.3	18.7	18.6	21.9	21.9	36.3	36.8	22.3	22.2	18.5	18	17.3	18.1
Loader_ 3_S5_6 7_8_9	30.9	30.7	25.4	28.2	19.4	15.7	13.7	13.4	27.5	20.3	17.4	14	16.4	14.7	19.9	19.2	16.7	15.9	16.9	16.1	19.4	18.6	31.1	30.5	19.8	19	16.6	15.7	15.3	15.6
IHR_1_ S7_8	30.6	30.7	22.9	26.3	26.7	16.4	23.7	22.4	30.1	24.7	12.7	11.3	10.3	7.3	13.4	12.8	10.9	10.3	10.2	9.7	12.8	11.9	25.9	25.5	14	13.5	10.3	9.9	11.6	12.1
Excavat or_2_S4 8_9	24.4	22.8	22.9	21.8	24.3	21.1	24	23	21.6	23	20	18.6	11.9	9.2	23.4	23.8	18.5	17.8					26	24.4	21.3	20.8				
Excavat or_1_S3 _4_7_8_ 9	23.2	22.6	21.8	21.5	23	20.1	22.5	22.2	24.2	26.2	20.3	18.9	20.5	17.7	28.9	28.7	18.2	17.4					24.5	24	23.4	22.7				
Loader_ 1_S3_4 7_8	23.2	22.6	21.5	21.2	22.8	19.9	22.3	22	22.2	21.7	20.3	18.8	20.4	17.1	29.3	28.9	18.2	17.4					24.6	24.1	23.4	22.8				
Excavat or_3_S4 8	20.8	20.1	19.6	19.1	20.5	18.4	20.2	20	21.3	23.5	20.2	18.5	12.2	8.2	21.6	21.8	17.8	17					22.2	21.6	18.8	18.3				
IHR_2_ S4_8	20.3	19.9	19.1	18.6	23.9	17.6	20	19.7	22.1	23.9	18.1	16	16.4	12.1	28.8	28.2	15.5	15	0	4.7			21.9	21.6	20.4	19.3				
Loader_ 2_S4_8 9	19.4	19.8	19.2	18.6	24.5	17.9	19.7	19.4	21.6	23	19.7	18	7.8	5.6	19.9	20.3	5.8	5.8					13.7	13.9	8.6	8.7				
Total	43.8	43.2	40.9	41.7	41.1	37.7	40.4	40	40.7	39.3	38	36.4	37.8	34.4	44.3	42.9	35.5	34.7	25.4	24.8	28.1	27.5	44.2	43.9	40.6	39.9	25.5	25	24.3	25

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.9 Point of Reception Impacts by Source for Scenario 9* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Screene r_S10	39. 8	39. 4	33. 5	37. 8	29. 4	25. 7	23. 6	23. 5	31. 8	27. 9	22. 8	20	22. 9	21. 1	26. 4	25. 6					25. 5	24. 5	35. 8	35. 3	25. 6	24. 6	24. 7	23. 5	23. 2	23.4
Crusher _S10_1 1	38	31. 9	36. 5	36. 7	38. 2	35. 5	37. 8	37. 5	39. 7	39	27. 1	26	35. 6	29. 2	40. 9	40. 3	33. 1	32. 1			29	28. 7	38. 1	37	37. 3	36. 5				
IHR_1_ S10	36	36	31. 5	35. 9	36. 5	27. 3	33. 9	33	36. 7	33. 5	20. 8	19. 3	19. 6	16. 4	21. 3	20. 8	18. 4	17. 8	18. 1	16. 8	20. 4	19. 7	32. 6	32. 4	21. 2	20. 6	20. 1	19. 1	18. 4	18.7
Loader_ 2_S10_ 11	32. 7	32. 4	26. 6	29. 5	21. 4	18. 4	16. 3	16. 3	27. 3	24	16. 7	15. 1	16. 3	14. 8	19. 5	18. 9					18. 8	18	28. 8	28. 4	18. 9	18	17. 5	16. 5	16. 5	16.8
Loader_ 3_S10	32. 7	32. 7	29. 8	32. 5	24. 7	21. 6	20. 1	19. 8	25. 1	24. 1	16. 7	15	16. 4	14. 9	19. 7	19. 1					18. 7	18	28. 9	28. 4	19	18. 1	18. 3	17. 5	16. 6	17
Excavat or_3_S1 0_11	32. 5	32. 1	27. 1	30. 2	22. 1	19. 2	17	17. 1	28. 6	24. 5	16. 3	14. 3	16. 4	15	19. 6	19					18. 8	18. 1	28. 6	28. 2	18. 9	18. 1	17. 3	16. 3	16. 6	17
Excavat or_2_S1 0_11	28. 2	29	24. 9	29. 6	21. 5	18. 4	15. 8	16. 2	28. 2	24. 5	15. 8	13. 7	15. 8	14	19. 5	19					18. 2	17. 5	28. 3	27. 9	18. 7	17. 9	14. 3	13. 8	16	16.3
Excavat or_1_S1 0_11	27. 8	26. 7	26. 5	30. 1	32. 4	28. 8	32. 4	31. 8	33. 6	32. 2	11. 7	10. 9	19	13	15. 5	14. 8	16. 5	15. 8			16. 8	16	26. 3	25. 9	20. 4	19. 7				
Loader_ 1_S10_ 11	18. 9	14. 2	20. 2	20. 4	22	19. 5	21. 6	21. 4	24. 7	24	12	11	18. 9	14	24	23. 2	16. 5	15. 6			16. 6	15. 8	26. 2	25. 7	20. 5	19. 7				
Total	44. 2	43. 1	40. 4	43. 1	41. 6	37. 5	40. 3	39. 8	43. 1	41. 4	30. 1	28. 6	36. 3	30. 6	41. 4	40. 7	33. 4	32. 5	18. 1	16. 8	32. 2	31. 6	42	41. 3	38	37. 2	27. 8	26. 8	26. 6	26.8

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.




Table A2.7.10 Point of Reception Impacts by Source for Scenario 10* - After Mitigation

Source	Evening and Nighttime Period (19:00 – 07:00)																													
	POR 1 PO W	POR 1 OPR	POR 2 PO W	POR 2 OPR	POR 3 PO W	POR 3 OPR	POR 4 PO W	POR 4 OPR	POR 5 PO W	POR 5 OPR	POR 6 PO W	POR 6 OPR	POR 7 PO W	POR 7 OPR	POR 8 PO W	POR 8 OPR	POR 9 PO W	POR 9 OPR	POR 10 PO W	POR 10 OP R	POR 11 PO W	POR 11 OP R	POR 12 PO W	POR 12 OP R	POR 13 PO W	POR 13 OP R	POR 14 PO W	POR 14 OP R	POR 15 PO W	POR 15 OPR
	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA	dBA
Crusher _S10_1 1	38	31.9	36.5	36.7	38.2	35.5	37.8	37.5	39.7	39	27.1	26	35.6	29.2	40.9	40.3	33.1	32.1			29	28.7	38.1	37	37.3	36.5				
Washpl ant	37.7	37.9	34.2	36.5	28.3	23.9	22.4	22.2	34.9	28	24.6	23.2	23.2	22.1	26.5	26	23.1	22.3	23.3	22.5	25.9	25.1	37	37.2	26.1	25.3	23.6	23.2	22.3	23.1
Generat or	36.4	36.6	29.9	32.6	23.8	20.3	18.7	18.6	33.8	25	20.4	18.8	18.6	17.5	22.7	22.6	18.5	18.3	18.7	18.6	21.9	21.9	36.3	36.8	22.3	22.2	18.5	18	17.3	18.1
IHR_1_ S11	36.2	36.2	31.3	36	36.5	27.3	33.9	33	36.6	33.6	20.8	19.3	19.6	16.4	21.3	20.8	18.2	17.6	18.1	16.8	20.6	19.9	32.5	32.1	21.1	20.5	20.2	19.2	18.4	18.8
Loader_ 2_S10_ 11	32.7	32.4	26.6	29.5	21.4	18.4	16.3	16.3	28.8	24	16.7	15.1	16.3	14.8	19.5	18.9					18.8	18	28.8	28.4	18.9	18	17.5	16.5	16.5	16.8
Excavat or_3_S1 0_11	32.5	32.1	27.1	30.2	22.1	19.2	17	17.1	28.6	24.5	16.4	14.7	16.4	15	19.6	19					18.8	18.1	28.6	28.2	18.9	18.1	17.3	16.3	16.6	17
Loader_ 3_S11	30.9	30.7	25.4	28.2	19.4	15.7	13.7	13.4	27.5	20.3	17.4	14	16.4	14.3	19.9	19.2	16.7	15.9	16.9	16.1	19.4	18.6	31.1	30.5	19.8	19	16.6	15.7	15.3	15.6
Excavat or_2_S1 0_11	28.2	29	24.9	29.6	21.5	18.4	15.8	16.2	28.2	24.5	15.8	13.7	15.8	14	19.5	19					18.2	17.5	28.3	27.9	18.7	17.9	14.3	13.8	16	16.3
Excavat or_1_S1 0_11	27.8	26.7	26.5	30.1	32.4	28.8	32.4	31.8	33.6	32.2	11.7	10.9	19	13	15.5	14.8	16.5	15.8			16.8	16	26.3	25.9	20.4	19.7				
Loader_ 1_S10_ 11	18.9	14.2	20.2	20.4	22	19.5	21.6	21.4	24.7	24	12	11	18.9	14	24	23.2	16.5	15.6			16.6	15.8	26.2	25.7	20.5	19.7				
Total	44.3	43.5	40.6	42.9	41.6	37.4	40.3	39.8	43.9	41.4	31	29.6	36.4	30.9	41.4	40.8	34	33.1	26	25.3	32.7	32.2	43.4	43.1	38.2	37.4	27.7	27	26.6	27.1

* Values at first floor window height (W) at 4.5 m or 2 m and Outdoor Point of Reception (OPR) at 1.5 m are given above as these where the most critical points at each receptor.





Table A2.8 Distance Source to Point of Reception

Source	PO R_1_ PO W	PO R_1_ OP R	PO R_2_ PO W	PO R_2_ OP R	PO R_3_ PO W	PO R_3_ OP R	PO R_4_ PO W	PO R_4_ OP R	PO R_5_ PO W	PO R_5_ OP R	PO R_6_ PO W	PO R_6_ OP R	PO R_7_ PO W	PO R_7_ OP R	PO R_8_ PO W	PO R_8_ OP R	PO R_9_ PO W	PO R_9_ OP R	PO R_10_ PO W	PO R_10_ OP R	PO R_11_ PO W	PO R_11_ OP R	PO R_12_ PO W	PO R_12_ OP R	PO R_13_ PO W	PO R_13_ OP R	PO R_14_ PO W	PO R_14_ OP R	PO R_15_ PO W	PO R_15_ OP R	
	183 795 80. 07	183 795 71. 88	183 798 39. 37	183 798 17. 37	183 799 84. 46	183 799 54. 46	183 800 64. 47	183 800 34. 47	183 797 35. 39	183 797 16. 72	183 795 65. 25	183 795 43. 8	183 784 64. 29	183 784 85. 55	183 782 86. 86	183 783 16. 86	183 776 85. 16	183 777 08. 64	183 781 80. 46	183 781 99. 52	183 792 17. 49	183 792 17. 49	183 791 23. 79	183 791 23. 79	183 780 13. 41	183 780 32. 89	183 814 31. 4	183 813 99. 4	183 814 07. 9	183 813 80. 8	
	497 774 2.3 2	497 771 5.2 2	497 741 5.8 9	497 739 4.7 2	497 737 1.5 4	497 736 1.9 4	497 734 2.7 4	497 734 2.7 4	497 685 0.0 7	497 686 7.2 7	497 590 4.6 8	497 592 4.3 8	497 599 1.2 8	497 600 5.7 3	497 658 6.7 3	497 658 6.7 3	497 806 7.5 1	497 804 3.3 8	497 878 1.8 5	497 875 9.0 4	497 894 9.2 7	497 891 9.2 7	497 781 3.7 6	497 778 3.7 6	497 749 2.9 2	497 747 0.4 8	497 730 0.6 0.6	497 729 8.6 8.6	497 712 4.1 8	497 713 7.4 6	
	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m
Crusher_S1_2 5 6	810	782	687	656	781	750	838	811	445	422	110 4	108 0	130 0	127 5	109 5	106 7	195 5	192 2	212 7	209 8	197 2	194 2	855	826	139 4	136 8	214 6	211 4	210 3	207 7	
Crusher_S3_4 7 8	111 4	108 7	107 4	104 4	117 8	114 7	123 7	121 0	798	780	112 0	109 1	965	942	695	667	175 9	172 6	209 2	206 4	213 6	210 6	999	970	113 6	110 7	253 8	250 6	248 8	246 2	
Crusher_S10_11	810	782	687	656	781	750	838	811	445	422	110 4	108 0	130 0	127 5	109 5	106 7	195 5	192 2	212 7	209 8	197 2	194 2	855	826	139 4	136 8	214 6	211 4	210 3	207 7	
Screeners_S1	247	219	332	317	483	457	568	539	687	665	159 8	157 8	184 3	181 9	153 5	151 1	191 9	189 0	185 2	182 2	147 8	144 9	503	485	150 6	148 7	192 3	189 1	192 6	189 7	
Screeners_S2	791	763	596	565	670	641	720	694	303	279	106 3	104 1	138 6	136 1	122 6	119 7	208 6	205 3	222 1	219 2	200 1	197 2	914	886	153 5	150 9	200 6	197 4	196 1	193 5	
Screeners_S3	150 7	147 9	140 5	137 4	148 3	145 4	152 8	150 4	991	981	898	869	577	552	573	544	200 2	196 9	244 1	241 4	254 7	251 7	141 2	138 3	134 5	131 5	273 5	270 4	266 2	263 9	
Screeners_S4	140 4	137 9	139 7	136 7	150 3	147 2	156 3	153 6	110 6	109 0	121 9	119 0	729	710	371	342	166 9	163 5	213 3	210 7	232 3	229 4	121 5	118 8	101 1	982	285 5	282 4	280 0	277 6	
Screeners_S10	388	364	196	169	333	303	413	383	517	498	145 8	144 0	181 2	178 8	156 9	154 3	209 0	205 9	204 6	201 6	164 7	161 8	696	677	164 4	162 2	178 1	174 9	177 2	174 3	
Washplant	325	297	316	296	464	436	547	518	610	588	151 8	149 8	178 0	175 6	149 2	146 7	194 8	191 8	191 1	188 8	155 8	152 8	559	539	151 1	149 1	191 2	188 0	190 8	187 9	
Generator	324	296	315	294	463	434	546	516	611	588	151 9	149 9	178 2	175 7	149 4	146 9	194 9	191 9	191 1	188 2	155 7	152 7	560	539	151 3	149 2	191 1	187 9	190 7	187 8	
Excavator_1_S1 2 5 6	789	761	648	617	738	708	794	767	404	380	110 1	107 8	133 5	131 0	114 0	111 2	199 0	195 7	214 6	211 7	196 8	193 8	860	831	143 4	140 8	210 0	206 8	205 7	203 1	
Excavator_1_S3 4 7 8 9	109 0	106 4	106 7	103 7	117 5	114 4	123 7	120 9	816	797	116 6	113 7	994	972	695	668	171 6	168 3	204 5	201 7	209 6	206 6	961	931	109 7	106 8	254 8	251 6	250 1	247 5	
Excavator_1_S10 11	789	761	648	617	738	708	794	767	404	380	110 1	107 8	133 5	131 0	114 0	111 2	199 0	195 7	214 6	211 7	196 8	193 8	860	831	143 4	140 8	210 0	206 8	205 7	203 1	
Excavator_2_S1 5	249	221	303	289	455	429	540	511	672	651	159 1	157 1	185 3	182 9	155 3	152 9	194 8	191 8	187 7	184 7	149 1	146 2	530	512	153 3	151 4	189 5	186 3	189 8	186 9	
Excavator_2_S2 6	767	739	558	528	630	600	678	653	277	252	107 8	105 7	142 6	140 0	126 7	123 8	210 8	207 5	222 8	219 8	198 8	195 8	911	883	156 4	153 8	196 7	193 5	192 2	189 6	
Excavator_2_S3 7	150 4	147 7	141 6	138 5	149 8	146 9	154 6	152 1	101 7	100 7	947	918	573	549	526	497	195 6	192 3	240 4	237 7	252 6	249 7	139 5	136 5	129 8	126 8	276 6	273 5	269 5	267 2	
Excavator_2_S4 8 9	144 0	141 4	143 4	140 5	154 0	150 9	160 0	157 3	114 0	112 4	123 1	120 2	703	685	335	306	166 7	163 4	214 6	211 9	235 0	232 1	124 6	121 9	100 8	978	289 0	285 9	283 4	281 0	
Excavator_2_S10 11	397	373	167	139	302	272	382	352	511	492	145 9	144 1	183 1	180 7	159 5	156 9	212 0	209 0	206 9	204 0	165 7	162 9	721	702	167 5	165 4	175 0	171 8	174 1	171 2	
Excavator_3_S1 5 9	254	226	333	318	485	459	570	541	683	660	159 3	157 2	183 6	181 2	152 9	150 5	191 8	188 8	185 4	182 4	148 3	145 4	504	486	150 3	148 3	192 5	189 4	192 8	189 9	
Excavator_3_S2 6	823	795	640	610	716	687	765	740	331	308	104 2	102 0	134 1	131 6	118 2	115 3	206 8	203 5	222 1	219 2	202 3	199 3	925	897	150 9	148 3	204 8	201 6	200 1	197 5	



Source	PO R 1_ PO W	PO R 1_ OP R	PO R 2_ PO W	PO R 2_ OP R	PO R 3_ PO W	PO R 3_ OP R	PO R 4_ PO W	PO R 4_ OP R	PO R 5_ PO W	PO R 5_ OP R	PO R 6_ PO W	PO R 6_ OP R	PO R 7_ PO W	PO R 7_ OP R	PO R 8_ PO W	PO R 8_ OP R	PO R 9_ PO W	PO R 9_ OP R	PO R 10_ PO W	PO R 10_ OP R	PO R 11_ PO W	PO R 11_ OP R	PO R 12_ PO W	PO R 12_ OP R	PO R 13_ PO W	PO R 13_ OP R	PO R 14_ PO W	PO R 14_ OP R	PO R 15_ PO W	PO R 15_ OP R	
	183 795 80. 07	183 795 71. 88	183 798 39. 37	183 798 17. 37	183 799 84. 46	183 799 54. 46	183 800 64. 47	183 800 34. 47	183 797 35. 39	183 797 16. 72	183 795 65. 25	183 795 43. 8	183 784 64. 29	183 784 85. 55	183 782 86. 86	183 783 16. 86	183 776 85. 16	183 777 08. 64	183 781 80. 46	183 781 99. 52	183 792 17. 49	183 792 17. 49	183 791 23. 79	183 791 23. 79	183 780 13. 41	183 780 32. 89	183 814 31. 4	183 813 99. 4	183 814 07. 9	183 813 80. 8	
	497 774 2.3 2	497 771 5.2 2	497 741 5.8 9	497 739 4.7 2	497 737 1.5 4	497 736 1.9 4	497 734 2.7 4	497 734 2.7 4	497 685 0.0 7	497 686 7.2 7	497 590 4.6 8	497 592 4.3 8	497 599 1.2 8	497 600 5.7 3	497 658 6.7 3	497 658 6.7 3	497 806 7.5 1	497 804 3.3 8	497 878 1.8 5	497 875 9.0 4	497 894 9.2 7	497 891 9.2 7	497 781 3.7 6	497 778 3.7 6	497 749 2.9 2	497 747 0.4 8	497 730 0.6 0.6	497 729 8.6 8	497 712 4.1 8	497 713 7.4 6	
	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m	m
Excavator_3_ S3 7	145 9	143 1	137 2	134 2	145 6	142 7	150 5	148 0	981	970	953	924	619	595	540	510	193 7	190 3	237 2	234 5	248 4	245 4	135 1	132 2	128 1	125 1	273 3	270 1	266 3	264 0	
Excavator_3_ S4 8	140 6	138 1	138 9	135 9	149 3	146 2	155 1	152 4	108 5	107 0	118 5	115 6	712	693	388	359	170 3	166 9	216 2	213 6	234 1	231 2	122 8	120 0	104 6	101 6	283 7	280 5	278 0	275 5	
Excavator_3_ S10 11	384	360	190	164	328	298	409	379	522	502	146 4	144 6	181 9	179 5	157 6	155 0	209 2	206 2	204 5	201 6	164 3	161 4	696	677	164 8	162 7	177 6	174 4	176 8	173 9	
Loader_1_S 1 2 5 6 9	806	778	690	660	786	755	844	817	457	434	111 4	109 0	129 9	127 4	108 9	106 1	194 3	191 0	211 5	208 6	196 4	193 4	846	816	138 2	135 6	215 5	212 3	211 3	208 7	
Loader_1_S3 4 7 8	111 8	109 1	109 1	106 2	119 8	116 7	125 9	123 2	830	812	115 4	112 6	967	944	673	645	172 3	168 9	206 2	203 4	212 1	209 1	987	958	109 9	107 0	256 6	253 4	251 7	249 2	
Loader_1_S 10 11	806	778	690	660	786	755	844	817	457	434	111 4	109 0	129 9	127 4	108 9	106 1	194 3	191 0	211 5	208 6	196 4	193 4	846	816	138 2	135 6	215 5	212 3	211 3	208 7	
Loader_2_S1 5	246	218	343	328	495	469	580	551	695	673	160 3	158 3	184 1	181 7	153 0	150 6	190 8	187 8	184 1	181 1	147 1	144 2	492	474	149 5	147 6	193 4	190 2	193 7	190 8	
Loader_2_S2 6	803	774	615	584	691	661	740	715	318	295	105 6	103 4	136 6	134 1	120 5	117 7	207 5	204 2	221 8	218 8	200 8	197 8	915	887	152 1	149 4	202 7	199 5	198 0	195 5	
Loader_2_S3 7	143 2	140 4	133 1	130 1	141 1	138 2	145 8	143 3	927	916	903	874	652	627	601	571	197 7	194 4	239 4	236 6	248 0	245 0	134 3	131 4	132 4	129 4	267 6	264 5	260 5	258 2	
Loader_2_S4 8 9	140 5	138 0	140 9	137 9	151 7	148 6	157 9	155 1	113 0	111 3	125 6	122 7	747	729	353	326	163 3	160 0	210 4	207 7	230 7	227 8	120 5	117 7	976	946	287 7	284 6	282 4	279 9	
Loader_2_S9	140 5	138 0	140 9	137 9	151 7	148 6	157 9	155 1	113 0	111 3	125 6	122 7	747	729	353	326	163 3	160 0	210 4	207 7	230 7	227 8	120 5	117 7	976	946	287 7	284 6	282 4	279 9	
Loader_2_S1 0 11	377	352	200	174	340	310	421	391	528	508	146 8	145 0	181 5	179 1	156 8	154 2	208 0	205 0	203 4	200 4	163 6	160 7	684	665	163 6	161 5	178 8	175 6	178 0	175 2	
Loader_3_S1	265	236	354	338	506	479	590	561	686	664	158 9	156 9	182 0	179 6	150 9	148 5	189 8	186 8	184 1	181 1	148 3	145 4	490	471	148 0	146 1	194 7	191 6	194 9	192 0	
Loader_3_S2	813	785	623	593	698	669	747	722	315	292	104 6	102 4	135 8	133 3	120 1	117 2	208 0	204 7	222 6	219 7	201 9	198 9	925	897	152 4	149 7	202 9	199 7	198 2	195 7	
Loader_3_S3	145 5	142 7	134 6	131 5	142 3	139 4	146 8	144 4	930	921	875	846	635	610	616	587	200 8	197 4	242 6	239 9	250 9	247 9	137 2	134 3	135 4	132 4	267 6	264 5	260 3	258 0	
Loader_3_S4	143 6	141 1	143 7	140 8	154 5	151 4	160 5	157 8	115 1	113 5	125 4	122 4	718	700	327	299	164 4	161 1	212 5	209 9	233 6	230 7	123 5	120 8	985	955	290 0	286 9	284 6	282 1	
Loader_3_S5 6 7 8 9	326	298	326	305	474	445	557	527	614	591	151 9	149 9	177 5	175 1	148 4	146 0	193 9	190 9	190 4	187 4	155 5	152 6	552	531	150 2	148 1	192 2	189 0	191 8	188 9	
Loader_3_S9	326	298	326	305	474	445	557	527	614	591	151 9	149 9	177 5	175 1	148 4	146 0	193 9	190 9	190 4	187 4	155 5	152 6	552	531	150 2	148 1	192 2	189 0	191 8	188 9	
Loader_3_S1 0	390	364	218	192	355	325	435	405	516	496	145 2	143 4	179 4	176 9	154 7	152 1	207 1	204 0	203 3	200 4	164 6	161 7	682	663	162 2	160 1	180 3	177 1	179 3	176 5	
Loader_3_S1 1	326	298	326	305	474	445	557	527	614	591	151 9	149 9	177 5	175 1	148 4	146 0	193 9	190 9	190 4	187 4	155 5	152 6	552	531	150 2	148 1	192 2	189 0	191 8	188 9	





Table A2.9 Sample Calculations – Scenario 1


Receiver															
Name: POR_1															
ID: POR_1 POW															
X: 18379580.07 m															
Y: 4977742.32 m															
Z: 196.59 m															

Line Source, ISO 9613, Name: "IHR_1", ID: "IHR_1_S1"																				
Nr.	X (m)	Y (m)	Z (m)	Refl.	DEN	Freq. (Hz)	Lw dB(A)	l/a dB	Optime dB	K0	Di (dB)	Adiv (dB)	Aatm (dB)	Agf (dB)	Afol (dB)	Ahou (dB)	Abar (dB)	Cmet (dB)	RL (dB)	Lr dB(A)
2	18379471.61	4977418.62	190.50	0	D	32	43.5	21.7	0.0	0.0	0.0	61.7	0.0	-4.2	0.7	0.0	4.8	0.0	0.0	2.2
2	18379471.61	4977418.62	190.50	0	D	63	53.5	21.7	0.0	0.0	0.0	61.7	0.0	-4.2	0.7	0.0	4.8	0.0	0.0	12.2
2	18379471.61	4977418.62	190.50	0	D	125	61.1	21.7	0.0	0.0	0.0	61.7	0.1	2.8	1.0	0.0	2.0	0.0	0.0	15.2
2	18379471.61	4977418.62	190.50	0	D	250	60.0	21.7	0.0	0.0	0.0	61.7	0.4	1.9	1.3	0.0	2.9	0.0	0.0	13.5
2	18379471.61	4977418.62	190.50	0	D	500	65.2	21.7	0.0	0.0	0.0	61.7	0.7	-0.9	1.7	0.0	4.8	0.0	0.0	19.0
2	18379471.61	4977418.62	190.50	0	D	1000	72.0	21.7	0.0	0.0	0.0	61.7	1.2	-1.2	2.0	0.0	4.9	0.0	0.0	25.1
2	18379471.61	4977418.62	190.50	0	D	2000	72.4	21.7	0.0	0.0	0.0	61.7	3.3	-1.2	2.7	0.0	5.0	0.0	0.0	22.6
2	18379471.61	4977418.62	190.50	0	D	4000	65.6	21.7	0.0	0.0	0.0	61.7	11.2	-1.2	3.0	0.0	5.2	0.0	0.0	7.4
2	18379471.61	4977418.62	190.50	0	D	8000	69.4	21.7	0.0	0.0	0.0	61.7	39.9	-1.2	4.0	0.0	5.5	0.0	0.0	-18.9
2	18379471.61	4977418.62	190.50	0	N	32	38.7	21.7	0.0	0.0	0.0	61.7	0.0	-4.2	0.7	0.0	4.8	0.0	0.0	-2.5
2	18379471.61	4977418.62	190.50	0	N	63	48.7	21.7	0.0	0.0	0.0	61.7	0.0	-4.2	0.7	0.0	4.8	0.0	0.0	7.4
2	18379471.61	4977418.62	190.50	0	N	125	56.3	21.7	0.0	0.0	0.0	61.7	0.1	2.8	1.0	0.0	2.0	0.0	0.0	10.4
2	18379471.61	4977418.62	190.50	0	N	250	55.2	21.7	0.0	0.0	0.0	61.7	0.4	1.9	1.3	0.0	2.9	0.0	0.0	8.8
2	18379471.61	4977418.62	190.50	0	N	500	60.4	21.7	0.0	0.0	0.0	61.7	0.7	-0.9	1.7	0.0	4.8	0.0	0.0	14.2
2	18379471.61	4977418.62	190.50	0	N	1000	67.2	21.7	0.0	0.0	0.0	61.7	1.2	-1.2	2.0	0.0	4.9	0.0	0.0	20.3
2	18379471.61	4977418.62	190.50	0	N	2000	67.6	21.7	0.0	0.0	0.0	61.7	3.3	-1.2	2.7	0.0	5.0	0.0	0.0	17.9
2	18379471.61	4977418.62	190.50	0	N	4000	60.8	21.7	0.0	0.0	0.0	61.7	11.2	-1.2	3.0	0.0	5.2	0.0	0.0	2.6
2	18379471.61	4977418.62	190.50	0	N	8000	64.6	21.7	0.0	0.0	0.0	61.7	39.9	-1.2	4.0	0.0	5.5	0.0	0.0	-23.7
2	18379471.61	4977418.62	190.50	0	E	32	38.7	21.7	0.0	0.0	0.0	61.7	0.0	-4.2	0.7	0.0	4.8	0.0	0.0	-2.5
2	18379471.61	4977418.62	190.50	0	E	63	48.7	21.7	0.0	0.0	0.0	61.7	0.0	-4.2	0.7	0.0	4.8	0.0	0.0	7.4
2	18379471.61	4977418.62	190.50	0	E	125	56.3	21.7	0.0	0.0	0.0	61.7	0.1	2.8	1.0	0.0	2.0	0.0	0.0	10.4
2	18379471.61	4977418.62	190.50	0	E	250	55.2	21.7	0.0	0.0	0.0	61.7	0.4	1.9	1.3	0.0	2.9	0.0	0.0	8.8
2	18379471.61	4977418.62	190.50	0	E	500	60.4	21.7	0.0	0.0	0.0	61.7	0.7	-0.9	1.7	0.0	4.8	0.0	0.0	14.2
2	18379471.61	4977418.62	190.50	0	E	1000	67.2	21.7	0.0	0.0	0.0	61.7	1.2	-1.2	2.0	0.0	4.9	0.0	0.0	20.3
2	18379471.61	4977418.62	190.50	0	E	2000	67.6	21.7	0.0	0.0	0.0	61.7	3.3	-1.2	2.7	0.0	5.0	0.0	0.0	17.9
2	18379471.61	4977418.62	190.50	0	E	4000	60.8	21.7	0.0	0.0	0.0	61.7	11.2	-1.2	3.0	0.0	5.2	0.0	0.0	2.6
2	18379471.61	4977418.62	190.50	0	E	8000	64.6	21.7	0.0	0.0	0.0	61.7	39.9	-1.2	4.0	0.0	5.5	0.0	0.0	-23.7
5	18379396.58	4977290.83	190.50	0	D	32	43.5	21.7	0.0	0.0	0.0	64.8	0.0	-4.7	0.0	0.0	2.9	0.0	0.0	2.2
5	18379396.58	4977290.83	190.50	0	D	63	53.5	21.7	0.0	0.0	0.0	64.8	0.1	-4.7	0.0	0.0	3.4	0.0	0.0	11.7
5	18379396.58	4977290.83	190.50	0	D	125	61.1	21.7	0.0	0.0	0.0	64.8	0.2	2.8	0.0	0.0	1.4	0.0	0.0	13.6
5	18379396.58	4977290.83	190.50	0	D	250	60.0	21.7	0.0	0.0	0.0	64.8	0.5	1.5	0.0	0.0	2.9	0.0	0.0	12.0
5	18379396.58	4977290.83	190.50	0	D	500	65.2	21.7	0.0	0.0	0.0	64.8	0.9	-1.3	0.0	0.0	4.5	0.0	0.0	18.0
5	18379396.58	4977290.83	190.50	0	D	1000	72.0	21.7	0.0	0.0	0.0	64.8	1.8	-1.6	0.0	0.0	4.6	0.0	0.0	24.1
5	18379396.58	4977290.83	190.50	0	D	2000	72.4	21.7	0.0	0.0	0.0	64.8	4.7	-1.6	0.0	0.0	4.7	0.0	0.0	21.5
5	18379396.58	4977290.83	190.50	0	D	4000	65.6	21.7	0.0	0.0	0.0	64.8	16.0	-1.6	0.0	0.0	4.7	0.0	0.0	3.4
5	18379396.58	4977290.83	190.50	0	D	8000	69.4	21.7	0.0	0.0	0.0	64.8	57.0	-1.6	0.0	0.0	4.8	0.0	0.0	-33.8
5	18379396.58	4977290.83	190.50	0	N	32	38.7	21.7	0.0	0.0	0.0	64.8	0.0	-4.7	0.0	0.0	2.9	0.0	0.0	-2.5
5	18379396.58	4977290.83	190.50	0	N	63	48.7	21.7	0.0	0.0	0.0	64.8	0.1	-4.7	0.0	0.0	3.4	0.0	0.0	6.9
5	18379396.58	4977290.83	190.50	0	N	125	56.3	21.7	0.0	0.0	0.0	64.8	0.2	2.8	0.0	0.0	1.4	0.0	0.0	8.8
5	18379396.58	4977290.83	190.50	0	N	250	55.2	21.7	0.0	0.0	0.0	64.8	0.5	1.5	0.0	0.0	2.9	0.0	0.0	7.3
5	18379396.58	4977290.83	190.50	0	N	500	60.4	21.7	0.0	0.0	0.0	64.8	0.9	-1.3	0.0	0.0	4.5	0.0	0.0	13.2
5	18379396.58	4977290.83	190.50	0	N	1000	67.2	21.7	0.0	0.0	0.0	64.8	1.8	-1.6	0.0	0.0	4.6	0.0	0.0	19.3
5	18379396.58	4977290.83	190.50	0	N	2000	67.6	21.7	0.0	0.0	0.0	64.8	4.7	-1.6	0.0	0.0	4.7	0.0	0.0	16.7
5	18379396.58	4977290.83	190.50	0	N	4000	60.8	21.7	0.0	0.0	0.0	64.8	16.0	-1.6	0.0	0.0	4.7	0.0	0.0	-1.4
5	18379396.58	4977290.83	190.50	0	N	8000	64.6	21.7	0.0	0.0	0.0	64.8	57.0	-1.6	0.0	0.0	4.8	0.0	0.0	-38.6
5	18379396.58	4977290.83	190.50	0	E	32	38.7	21.7	0.0	0.0	0.0	64.8	0.0	-4.7	0.0	0.0	2.9	0.0	0.0	-2.5
5	18379396.58	4977290.83	190.50	0	E	63	48.7	21.7	0.0	0.0	0.0	64.8	0.1	-4.7	0.0	0.0	3.4	0.0	0.0	6.9
5	18379396.58	4977290.83	190.50	0	E	125	56.3	21.7	0.0	0.0	0.0	64.8	0.2	2.8	0.0	0.0	1.4	0.0	0.0	8.8
5	18379396.58	4977290.83	190.50	0	E	250	55.2	21.7	0.0	0.0	0.0	64.8	0.5	1.5	0.0	0.0	2.9	0.0	0.0	7.3
5	18379396.58	4977290.83	190.50	0	E	500	60.4	21.7	0.0	0.0	0.0	64.8	0.9	-1.3	0.0	0.0	4.5	0.0	0.0	13.2
5	18379396.58	4977290.83	190.50	0	E	1000	67.2	21.7	0.0	0.0	0.0	64.8	1.8	-1.6	0.0	0.0	4.6	0.0	0.0	19.3
5	18379396.58	4977290.83	190.50	0	E	2000	67.6	21.7	0.0	0.0	0.0	64.8	4.7	-1.6	0.0	0.0	4.7	0.0	0.0	16.7
5	18379396.58	4977290.83	190.50	0	E	4000	60.8	21.7	0.0	0.0	0.0	64.8	16.0	-1.6	0.0	0.0	4.7	0.0	0.0	-1.4
5	18379396.58	4977290.83	190.50	0	E	8000	64.6	21.7	0.0	0.0	0.0	64.8	57.0	-1.6	0.0	0.0	4.8	0.0	0.0	-38.6
43	18379420.14	4977352.39	190.50	0	D	32	43.5	22.1	0.0	0.0	0.0	63.5	0.0	-4.5	0.0	0.0	3.0	0.0	0.0	3.5



Appendix 3

Instrument Calibration Certificates





www.pylonelectronics.com

Pylon Electronics Inc.
147 Colonnade Road
Ottawa, ON K2E 7L9

Page 1 of 1

CERTIFICATE OF CALIBRATION

Description	SOUND LEVEL CALIBRATOR	Work Order	N0833134
Model Number	4231	Serial Number	2730374
Instrument Id	N/A	Cal Procedure	33K3-4-2871-1
Manufacturer	BRUEL & KJAER	Cal Date	30 Jan 2020
Customer Name	FREEFIELD LTD.	Recall Cycle	52 Weeks
		Next Cal Date	30 Jan 2021
		Purchase Order	Credit Card

Calibration Environment: Temperature 23.0 °C Relative Humidity 35.2 %RH

Received Condition: Within Tolerance

Completed Condition: Within Tolerance

Remarks: Optimized sound level.

Standards Used to Establish Traceability

Instrument Type	Model	Asset #	Cal Due Date
4145 BRUEL&KJAER 1" MICROPHONE	4145	240-054	4 Dec 2020
1/2" MICROPHONE	4166	240-709	18 Jun 2020
PISTONPHONE	4220	354-017	1 Apr 2020
FFT SIGNAL ANALYZER SYSTEM	3550	354-759	10 Oct 2020
MICROPHONE PREAMP	2639T	355-164	27 Feb 2020

Pylon certifies that, at the time of calibration, the above listed instrument meets or exceeds all of the specifications defined on the Test Data Sheet (TDS), unless otherwise indicated. The Certificate received and completed conditions and the TDS specifications are based on the procedure(s) and/or specification(s) referenced on the TDS unless otherwise indicated. Any statement of compliance is made without taking measurement uncertainty into account and is based on the instrument's performance against the test limits documented on the test data sheet.

The above listed instrument has been calibrated using standards that are traceable to the International System of Units (SI) through a National Metrological Institute (such as NRC or NIST). Pylon's quality system meets the requirements of ISO/IEC 17025:2005. Unless otherwise specified, Pylon maintains a minimum of a 4:1 ratio between the equipment under test and the measurement system.

This report consists of two parts with separate page numbering schemes; the Certificate of Calibration and the Test Data Sheet (TDS). Copyright of this report is owned by the issuing laboratory and may not be reproduced, other than in full, except with the prior written permission of the issuing laboratory.

Test data As Found and Final (as left) results are the same unless reported otherwise. Certificate remarks identify if adjustments were performed.

pylcent1

Metrologist : 062

Quality Assurance: 301

Date of Issue: 30 Jan 2020

F083 Rev 15

HALIFAX


MONTREAL

OTTAWA

TORONTO

EDMONTON

CALGARY





Calibration Test Data

Page 1 of 1

Description: **SOUND LEVEL CALIBRATOR**

Work order: **N0833134**

Model: 4231

Serial: 2730374

Customer ID.: N/A


Procedure: **33K3-4-2871-1**

Manufacturer: **BRUEL & KJAER**

Proc. Rev.: 30-Oct-2006

Customer: **FREEFIELD LTD.**

Cal Date: 30-Jan-2020

[illegible]



www.pylonelectronics.com

Pylon Electronics Inc.
147 Colonnade Road
Ottawa, ON K2E 7L9

Page 1 of 1

CERTIFICATE OF CALIBRATION

Description SOUND ANALYZER
Model Number 2270
Instrument Id N/A
Manufacturer BRUEL & KJAER
Customer Name FREEFIELD LTD.

Work Order N0833130
Serial Number 3008643
Cal Procedure BE1713-32
Cal Date 30 Jan 2020
Recall Cycle 52 Weeks
Next Cal Date 30 Jan 2021
Purchase Order Credit Card

Calibration Environment: Temperature 23.0 °C Relative Humidity 35.2 %RH

Received Condition: Within Tolerance

Completed Condition: Within Tolerance

Remarks: Unit calibrated with Preamp ZC 0032 S/N 23073 AND MIC 4189 S/N 2985656

Standards Used to Establish Traceability

<u>Instrument Type</u>	<u>Model</u>	<u>Asset #</u>	<u>Cal Due Date</u>
SOUND LEVEL CALIBRATOR	4231	240-1151	17 Sep 2020
PISTONPHONE	4220	354-017	1 Apr 2020

Pylon certifies that, at the time of calibration, the above listed instrument meets or exceeds all of the specifications defined on the Test Data Sheet (TDS), unless otherwise indicated. The Certificate received and completed conditions and the TDS specifications are based on the procedure(s) and/or specification(s) referenced on the TDS unless otherwise indicated. Any statement of compliance is made without taking measurement uncertainty into account and is based on the instrument's performance against the test limits documented on the test data sheet.

The above listed instrument has been calibrated using standards that are traceable to the International System of Units (SI) through a National Metrological Institute (such as NRC or NIST). Pylon's quality system meets the requirements of ISO/IEC 17025:2005. Unless otherwise specified, Pylon maintains a minimum of a 4:1 ratio between the equipment under test and the measurement system.

This report consists of two parts with separate page numbering schemes; the Certificate of Calibration and the Test Data Sheet (TDS). Copyright of this report is owned by the issuing laboratory and may not be reproduced, other than in full, except with the prior written permission of the issuing laboratory.

Test data As Found and Final (as left) results are the same unless reported otherwise. Certificate remarks identify if adjustments were performed.

pylcert1

Metrologist : 062

Quality Assurance: 301

Date of Issue: 30 Jan 2020

F083 Rev 15

HALIFAX


MONTREAL

OTTAWA

TORONTO

EDMONTON

CALGARY






Calibration Test Data

Description: **SOUND ANALYZER**
Model: **2270**
Customer ID.: **N/A**
Manufacturer: **BRUEL & KJAER**
Customer: **FREEFIELD LTD.**

Work order: **N0833130**
Serial: **3008643**
Procedure: **BE1713-32**
Proc. Rev.: **23-Feb-2016**
Cal Date: **30-Jan-2020**


[illegible]

Appendix 4

Manufacturers Data

Contents:

- Manufacturers Data for Cummins 600kW diesel generator used to provide power to the wash plant
- Manufacturers Data for Silex Silencer Model JB 6.



Manufacturers Data for Cummins 600kW diesel generator.



Sound data 600DQPAA 60 Hz

Sound pressure level @ 7 meters, dB(A)

See notes 1-8 listed below

Configuration		Measurement location number								Average
		1	2	3	4	5	6	7	8	
Standard - unhooded	Infinite exhaust	86.70	91.40	89.80	93.30	91.10	93.10	93.20	92.10	91.70
F200 weather	Mounted muffler	93.50	89.30	83.60	89.10	89.10	89.70	81.10	87.20	89.10
F201 – quiet site II first stage	Mounted muffler	87.30	78.60	77.60	77.40	78.60	77.70	74.10	78.00	80.70
F202 – quiet site II second stage	Mounted muffler	72.60	72.10	75.20	72.70	77.80	75.90	72.50	75.30	74.70

Sound power level, dB(A)

See notes 2-6, 9 and 10 listed below

Configuration		Octave band center frequency (Hz)									Overall sound power level
		31.5	63	125	250	500	1000	2000	4000	8000	
Standard - unhooded	Infinite exhaust	66.00	93.80	105.10	109.10	112.40	112.90	114.40	110.90	111.80	120.20
F200 weather	Mounted muffler	73.10	94.00	104.20	109.50	109.70	111.00	111.50	109.90	109.10	118.30
F201 – quiet site II first stage	Mounted muffler	73.50	93.20	103.10	104.80	102.10	101.70	105.50	101.30	100.40	111.70
F202 – quiet site II second stage	Mounted muffler	66.10	93.30	102.90	97.50	92.50	98.10	98.80	94.00	88.40	106.70

Exhaust sound power level, dB(A)

Open exhaust (no muffler rated load)	RPM	Applied load	Octave band center frequency (Hz)									Overall sound power level
			31.5	63	125	250	500	1000	2000	4000	8000	
	1800	600KW	64.90	97.40	112.50	120.20	121.80	122.90	124.90	121.10	109.30	129.70


Note:

- Position 1 faces the generator front. The positions proceed around the generator set in a counter-clockwise direction in 45° increments. All positions are at 7 m (23 ft) from the surface of the generator set and 1.2 m (48 in) from floor level.
- Sound levels are subject to instrumentation, measurement, installation and manufacturing variability.
- Sound data with remote-cooled generator sets are based on rated loads without cooling fan noise.
- Sound levels for aluminium enclosure are approximately 2 dB(A)s higher than listen sound levels for steel enclosures.
- Sound data for generator set with infinite exhaust do not include exhaust noise.
- Data is based on full rated load with standard radiator-cooling fan package.
- Sound pressure levels are measured per ANSI S1.13 and ANSI S12.18, as applicable.
- Reference sound pressure is 20 µPa.
- Sound power levels per ISO 3744 and ISO 8528-10, as applicable.
- Reference power = 1 pw (10⁻¹² W).
- Exhaust sound power levels are per ISO 6798, as applicable.

Cummins Inc.

Data and specification subject to change without notice

MSP-1206
(10/17)



Manufacturers Data for Silex Silencer Model JB 6.

www.silex.com

JB

CRITICAL CYLINDRICAL SILENCERS

25 to 32 dBA Noise Reduction


SILENCER SELECTION

For immediate assistance to select the appropriate silencer that best suits your application's acoustical and backpressure requirements contact Silex Innovations. Or, use our exclusive silencer sizing and selection program, found at www.silex.com.

PERFORMANCE & MATERIALS

The critical grade series are reactive silencers with good acoustical performance. All of the silencers are manufactured from light to heavy gauge steel and finished with high temperature black paint. A drain is included as a standard component on the silencer.

TYPICAL ATTENUATION CURVE



DIMENSIONS

Model	ØA in(mm)	ØB in(mm)	C in(mm)	D in(mm)	F** in(mm)	G in(mm)	H in(mm)	Wgt lb(kg)
JB-1.5	1.5	9(229)	24(610)	30(762)	4(102)	7.5(191)	27(686)	23(10)
JB-2	2	9(229)	24(610)	30(762)	4.5(114)	7.5(191)	27(686)	24(11)
JB-2.5	2.5	10(254)	28(711)	34(864)	5(127)	8(203)	31(787)	34(15)
JB-3	3	12(305)	32(813)	38(660)	5.5(140)	9(229)	35(889)	46(21)
JB-3.5	3.5	14(356)	36(914)	42(1067)	6(152)	10(254)	39(991)	65(29)
JB-4	4	14(356)	40(1016)	48(1219)	6(152)	11(279)	44(1118)	77(35)
JB-5	5	16(406)	49(1245)	57(1448)	7(178)	12(305)	53(1346)	107(49)
JB-6	6	18(457)	55(1397)	63(1600)	8(203)	13(330)	59(1499)	135(61)
JB-8	8	22(559)	66(1676)	74(1880)	9.5(241)	15(381)	70(1778)	208(94)
JB-10	10	26(660)	81(2057)	89(2261)	11.5(292)	17(432)	85(2159)	370(168)
JB-12	12	30(762)	94(2388)	102(2591)	13(330)	19(483)	98(2489)	505(229)
JB-14	14	36(914)	99(2515)	109(2769)	15.5(394)	23(584)	104(2642)	642(291)
JB-16	16	40(1016)	109(2769)	119(3023)	16.5(419)	25(635)	114(2896)	971(440)
JB-18	18	45(1143)	117(2972)	127(3226)	18(457)	27.5(699)	122(3099)	1167(529)
JB-20	20	50(1270)	127(3226)	137(3480)	20.5(521)	30(762)	132(3353)	1669(757)
JB-22	22	54(1372)	139(3531)	149(3785)	22.5(572)	32(813)	144(3658)	1972(894)
JB-24	24	60(1524)	152(3861)	162(4115)	24(610)	35(889)	157(3988)	2384(1081)
JB-26	26	64(1626)	173(4394)	183(4648)	25.5(648)	37(940)	178(4521)	2854(1295)
JB-28	28	68(1727)	190(4826)	200(5080)	26.5(673)	39(991)	195(4953)	3278(1487)
JB-30	30	72(1829)	206(5232)	216(5486)	28(711)	41(1041)	211(5359)	3777(1713)


**For F dimension other than that specified, please contact Silex Innovations.
Available in sizes up to 60" inlet.

OPTIONS

- Aluminized steel, 304L or 316L stainless steel
- Dual inlet or custom inlet / outlet configurations
- Thermal insulation blankets to suit all configurations
- Mounting brackets, gussets and lifting lugs

Metric dimensions rounded to nearest mm. Dimensions and weights are nominal and may vary slightly in production models. On silencers 4" and larger the inlet and outlet are flanged, manufactured from minimum 1/2" thick plate and drilled to ANSI class 150.
The default material used is aluminized steel, however NPG reserves the right to substitute to carbon steel due to material availability, gauge and size limitations.

TYPICAL ORIENTATIONS



Corporate Headquarters
1560 Williams Drive
Stoughton, WI 53589
Tel: 608-719-1800



silex.com

Silex: 1-800-387-7818
Sales/Quote Email: Silex.Sales@npgsolutions.com
Order Email: Silex.Orders@npgsolutions.com

35

